

High IP3 Frequency Mixer

Level 17 (LO Power +17 dBm) 1400 to 2400 MHz


Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
RF Power	200mW
IF Current	40mA
Permanent damage may occur if any of these limits are exceeded.	

Pin Connections

LO	2
RF	1
IF	3
GROUND	4,5,6


Outline Drawing



Outline Dimensions (inch mm)

A	B	C	D	E	F	G	H	J	K
.38	.50	.23	.020	.075	.250	.425	.187	.050	.050
9.65	12.70	5.84	0.51	1.91	6.35	10.80	4.75	1.27	1.27
L	M	N	P	Q	R	S	T	wt.	
.070	.270	.540	.060	.095	.445	.208	.415	grams	
1.78	6.86	13.72	1.52	2.41	11.30	5.28	10.54	0.8	

Demo Board MCL P/N: TB-12 Suggested PCB Layout (PL-079)



- NOTE: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS .030" ± .002". COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. GROUND PAD SHALL BE FREE OF SOLDER MASK IF REQUIRED FOR SOLDERING.
3. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
- Legend:
Blue box: DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER), SEE NOTE 2.
Hatched box: DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK


Features

- low conversion loss, 7.0 dB typ.
- high IP3, 29 dBm typ.
- good L-R isolation, 32 dB typ.; & L-I isolation, 36 dB typ.

Applications

- base stations
- cellular
- communications
- DCS
- PCS

SYM-24DH+ SYM-24DH



CASE STYLE: TTT167
PRICE: \$9.95 ea. QTY (1-9)

+ RoHS compliant in accordance
with EU Directive (2002/95/EC)

The +Suffix identifies RoHS Compliance. See our web site
for RoHS Compliance methodologies and qualifications.

Electrical Specifications


FREQUENCY (MHz)		CONVERSION LOSS (dB)		LO-RF ISOLATION (dB)		LO-IF ISOLATION (dB)		IP3 at center band (dBm)		
LO/RF	IF	Mid-Band m	Total Range							
f_L - f_U		$\overline{X}$	σ	Max.		Typ.	Min.			
1400-2400	10-250	7.0	.20	9.3		32	22	36	23	29

1 dB COMP.: +14 dBm typ.

Typical Performance Data

Frequency (MHz)		Conversion Loss (dB)	Isolation L-R (dB)	Isolation L-I (dB)	VSWR RF Port (:1)	VSWR LO Port (:1)
RF	LO	LO +17dBm	LO +17dBm	LO +17dBm	LO +17dBm	LO +17dBm
1400.00	1430.00	6.43	34.31	47.72	2.53	1.09
1418.18	1448.18	6.38	34.13	48.31	2.49	1.08
1436.36	1466.36	6.52	33.90	49.48	2.48	1.06
1454.55	1484.55	6.56	33.73	49.50	2.46	1.04
1490.91	1520.91	6.42	33.42	50.50	2.38	1.02
1527.27	1557.27	6.39	33.23	51.77	2.25	1.01
1563.64	1593.64	6.48	32.99	51.26	2.17	1.03
1600.00	1630.00	6.35	32.79	50.00	2.03	1.05
1671.88	1701.88	6.49	32.33	50.20	1.86	1.08
1715.63	1745.63	6.45	32.12	50.44	1.81	1.09
1737.50	1767.50	6.59	32.09	49.78	1.81	1.10
1759.38	1789.38	6.70	32.03	49.47	1.78	1.11
1803.13	1833.13	6.70	32.25	48.37	1.81	1.13
1846.88	1876.88	7.05	32.45	48.05	1.84	1.15
1890.63	1920.63	7.16	32.55	46.45	1.90	1.17
1934.38	1964.38	7.38	32.81	45.93	1.94	1.20
1956.25	1986.25	7.52	32.91	45.18	1.96	1.21
2000.00	2030.00	7.53	33.09	44.01	2.02	1.23
2166.67	2196.67	8.12	34.12	39.40	2.04	1.28
2400.00	2430.00	8.08	33.99	37.27	2.08	1.35

Electrical Schematic



Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine www.minicircuits.com Provides ACTUAL Data Instantly at [minicircuits.com](http://www.minicircuits.com)

IF/RF MICROWAVE COMPONENTS







For detailed performance specs
& shopping online see web site

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuits' applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

REV. C
M112207
SYM-24DH
EDR-5227
DJ/TD/CP/AM
091006
Page 1 of 2

Performance Charts

SYM-24DH+ SYM-24DH



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine www.minicircuits.com Provides ACTUAL Data Instantly at [minicircuits.com](http://www.minicircuits.com)

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

For detailed performance specs
& shopping online see web site