

High IP3

Frequency Mixer

Level 17 (LO Power +17 dBm) 100 to 1800 MHz

TUF-18DHSM+



CASE STYLE: NNN150
PRICE: \$26.20 ea. QTY (1-9)

+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix has been added in order to identify RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.

Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
RF Power	200mW
IF Current	40mA
Permanent damage may occur if any of these limits are exceeded.	

Pin Connections

LO	4
RF	1
IF	2
GROUND	3
CASE GROUND	3

Features

- low conversion loss, 7.3 dB typ.
- excellent L-R isolation, 41 dB typ.
- high IP3, 27 dBm typ.
- wideband, 100 to 1800 MHz
- rugged welded construction

Applications

- airphone
- cellular
- PCS
- PCN

Electrical Specifications

FREQUENCY (MHz)		CONVERSION LOSS (dB)				LO-RF ISOLATION (dB)		LO-IF ISOLATION (dB)		IP3 @ CENTER BAND (dBm)
LO/RF	IF	Mid-Band m	$\bar{X}$	σ	Max.	Total Range Max.	Typ.	Min.	Typ.	Min.
$f_L - f_U$										
100-1800	50-750	7.3	0.15	8.5	9.0		41	23	33	20
										27

1 dB COMP.: +10 dBm typ.


m= mid band [f_L to $f_U/2$]

Typical Performance Data


Frequency (MHz)		Conversion Loss (dB)	Isolation L-R (dB)	Isolation L-I (dB)	VSWR RF Port (:1)	VSWR LO Port (:1)
RF	LO	LO +17dBm	LO +17dBm	LO +17dBm	LO +17dBm	LO +17dBm
100.00	130.00	7.20	48.50	35.20	2.27	1.15
230.77	260.77	7.23	51.20	35.80	2.23	1.11
300.00	330.00	7.08	52.30	36.30	2.25	1.16
361.54	391.54	7.12	50.40	36.90	1.89	1.18
492.31	522.31	7.10	48.70	36.00	1.92	1.29
500.00	530.00	7.09	48.50	36.00	1.84	1.28
600.00	630.00	7.11	48.10	34.80	1.61	1.28
623.08	653.08	7.07	47.50	34.70	1.52	1.30
700.00	730.00	7.06	46.20	33.60	1.44	1.36
753.85	783.85	7.07	45.90	32.80	1.56	1.38
884.62	914.62	7.09	43.80	31.70	1.27	1.46
1000.00	1030.00	7.04	44.40	30.10	1.22	1.51
1015.39	1045.39	7.03	43.80	30.00	1.25	1.51
1146.15	1176.15	7.23	43.40	29.50	1.32	1.77
1276.92	1306.92	7.31	42.20	28.80	1.68	2.25
1407.69	1437.69	7.34	39.20	29.40	2.30	2.68
1500.00	1530.00	7.38	37.00	29.10	3.57	2.96
1538.46	1568.46	7.38	36.80	28.60	3.57	2.96
1669.23	1699.23	7.39	36.20	28.10	2.92	2.76
1800.00	1830.00	7.83	35.40	28.40	2.76	2.55

Outline Drawing

NOTE: BLUE BEAD INDICATES PIN #1. PIN NUMBERS DO NOT APPEAR ON UNIT FOR REFERENCE ONLY.



PCB Land Pattern




Suggested Layout

Tolerance to be within ±.002

Outline Dimensions (inch/mm)


A	B	C	D	E	F	G
.50	.48	.255	.240	.23	.21	.06
12.70	12.19	6.48	6.10	5.84	5.33	1.52
H	J	K	L	M	N	wt
.100	.09	.16	.020	.09	.005	grams
2.54	2.29	4.06	0.51	2.29	0.13	1.9

Demo Board MCL PIN : TB-201 Suggested PCB Layout (PL-081)



- NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS 0.030" ± 0.002". COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
3. DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
4. DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

Electrical Schematic



Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED

For detailed performance specs & shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

IF/RF MICROWAVE COMPONENTS

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuits' applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits' standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

REV. C
M102713
TUF-18DHSM+
DJ/TD/CP/AM
091006
Page 1 of 2

