

Surface Mount High Reliability Mixer

ADE-R1L+

Level 3 (LO Power +3 dBm) 2 to 500 MHz




Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
RF Power	50mW
IF Current	40mA
Permanent damage may occur if any of these limits are exceeded.	


Pin Connections

LO	6
RF	3
IF	2
GROUND	1,4,5

Outline Drawing




PCB Land Pattern



Outline Dimensions (inch/mm)

A	B	C	D	E	F	G
.272	.310	.220	.100	.112	.055	.100
6.91	7.87	5.59	2.54	2.84	1.40	2.54
H	J	K	L	wt		
.030	.026	.065	.300	grams		
0.76	0.66	1.65	7.62	0.20		

Demo Board MCL P/N: TB-03 Suggested PCB Layout (PL-052)



Features

- hermetically sealed ceramic quad
- low conversion loss, 5.6 dB typ.
- excellent L-R isolation, 55 dB typ.
- low profile package
- aqueous washable
- protected by US patent 6,133,525

Applications

- cellular
- instrumentation

CASE STYLE: CD542
PRICE: \$4.35 ea. QTY. (20)

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications



Available Tape and Reel at no extra cost

Reel Size	Devices/Reel
7"	20, 50, 100, 200, 500
13"	500, 1000

Electrical Specifications

FREQUENCY (MHz)	CONVERSION LOSS (dB)	LO-RF ISOLATION (dB)			LO-IF ISOLATION (dB)			IP3 at center band (dBm)
		L	M	U	L	M	U	
2-500	DC-500	68	55	44	60	45	35	14


1 dB COMP: 0 dBm typ.
See Notes below.

L = low range [f_L to $10 f_L$] M = mid range [$10 f_L$ to $f_U/2$] U = upper range [$f_U/2$ to f_U]
m = mid band [$2f_L$ to $f_U/2$]

Typical Performance Data

Frequency (MHz)	Conversion Loss (dB)		Isolation (dB)		VSWR RF Port (:1)		VSWR LO Port (:1)	
	LO	+3dBm	LO	+3dBm	LO	+3dBm	LO	+3dBm
2.00	32.00	6.61	65.26	57.10	1.65	1.65		
6.00	36.00	5.88	65.10	56.12	1.28	1.64		
8.00	38.00	5.76	65.14	55.62	1.23	1.65		
10.00	40.00	5.69	65.06	55.20	1.21	1.65		
59.00	89.00	5.63	62.33	47.86	1.11	1.65		
108.00	138.00	5.66	57.94	44.52	1.10	1.66		
157.00	187.00	5.66	54.76	42.14	1.08	1.64		
206.00	236.00	5.69	51.63	41.58	1.07	1.70		
230.50	260.50	5.75	50.62	40.71	1.07	1.71		
255.00	285.00	5.74	49.85	39.80	1.06	1.67		
279.50	309.50	5.76	48.93	39.70	1.05	1.74		
304.00	334.00	5.79	47.42	39.78	1.05	1.83		
328.50	358.50	5.86	46.02	39.31	1.05	1.78		
353.00	383.00	5.87	44.99	38.34	1.05	1.73		
377.50	407.50	5.90	44.68	37.39	1.06	1.85		
402.00	432.00	6.00	44.64	36.12	1.08	1.94		
426.50	456.50	6.05	44.52	34.99	1.09	1.84		
451.00	481.00	6.09	43.69	33.80	1.10	1.83		
475.50	505.50	6.09	43.36	33.28	1.11	2.02		
500.00	530.00	6.17	43.65	33.31	1.12	2.03		

Electrical Schematic



Mini-Circuits
ISO 9001 ISO 14001 AS 9100 CERTIFIED
The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com
IF/RF MICROWAVE COMPONENTS

For detailed performance specs & shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

REV. OR
M109914
ADE-R1L+
ED-12872/1
WL/TD/CP/AM
120628
Page 1 of 2

