

High Reliability Mixer

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications


Permanent damage may occur if any of these limits are exceeded.

LO	4
RF	1
IF	2
GROUND	3
CASE GROUND	3

NOTE: BLUE BEAD INDICATES PIN #1.
PIN NUMBERS DO NOT APPLY ON UNIFORM REFERENCE ONLY.

The left diagram shows a cross-section of a component with dimensions C, D, N MAX, and J. The right diagram shows a top view of a component with dimensions A, B, E, F, G, H, and M. It features four pins labeled 1, 2, 3, and 4, with pin 1 marked with a blue bead. Pin 1 is labeled '#1 TYP' and pin 4 is labeled '#4 TYP'.

PCB Land Pattern



Suggested Layout,
Tolerance to be within $\pm .002$

A	B	C	D	E	F	G
.50	.48	.255	.240	.23	.21	.06
12.70	12.19	6.48	6.10	5.84	5.33	1.52
H	J	K	L	M	N	wt
.100	.09	.16	.020	.09	.005	grams
2.54	2.29	4.06	0.51	2.29	.013	1.9

Figure 1 is a detailed cross-sectional view of the package. It shows the internal structure, including the PIN1, the .064 LINE WIDTH, 3 PL. (SEE NOTE BELOW), the .030 and .020 2 PL. dimensions, the PACKAGE OUTLINE, the .090 TYP dimension, the .038 and .072 dimensions, the .080 TYP dimension, the .020 PTH, 20 PL. FOR GROUND dimension, and the .020 2 PL. dimension.

NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS $0.030" \pm 0.002"$; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.

2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.

 DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)

 DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

- hermetically sealed ceramic quad
- low conversion loss, 6.5 dB typ.
- high isolation L-R, 48 dB typ.
- wideband, 20 to 1500 MHz
- rugged welded construction
- shielded metal case

- satellite distribution
- cellular
- ISM/GSM

FREQUENCY (MHz)		CONVERSION LOSS (dB)				LO-RF ISOLATION (dB)						LO-IF ISOLATION (dB)						IP3 at center band (dBm)	
LO/Rf	IF	Mid-Band m				Total Range Max.	L		M		U		L		M		U		Typ.
		$\bar{X}$	σ	Max.	Typ. Min.		Typ. Min.	Typ. Min.	Typ. Min.	Typ. Min.	Typ. Min.	Typ. Min.	Typ. Min.	Typ. Min.					
20-1500	DC-1200	6.5	0.05	9.0	9.0	55	42	48	35	43	32	40	25	30	18	23	10	12	

1 dB COMP.: +1 dBm typ.

L = low range [f_L to $10 f_L$] M = mid range [$10 f_L$ to $f_U/2$] U = upper range [$f_U/2$ to f_U]
m = mid band [$2f_L$ to $f_U/2$]

Frequency (MHz)		Conversion Loss (dB)	Isolation L-R (dB)	Isolation L-I (dB)	VSWR RF Port (:1)	VSWR LO Port (:1)
RF	LO	LO +7dBm	LO +7dBm	LO +7dBm	LO +7dBm	LO +7dBm
10.10	40.10	5.87	61.00	45.39	1.82	2.58
50.10	80.10	5.81	57.81	40.02	1.13	2.32
110.10	140.10	5.59	53.70	36.25	1.04	2.44
150.10	180.10	5.68	51.95	34.52	1.07	2.31
210.10	240.10	5.68	50.41	32.61	1.13	2.39
250.10	280.10	5.74	49.16	31.60	1.17	2.31
310.10	340.10	5.78	48.33	30.21	1.24	2.37
350.10	380.10	5.82	47.76	29.49	1.29	2.34
450.10	480.10	5.97	46.00	28.06	1.45	2.36
510.10	540.10	6.12	45.60	27.50	1.58	2.39
610.10	640.10	6.25	44.37	26.83	1.83	2.41
710.10	740.10	6.53	43.52	26.35	2.16	2.45
810.10	840.10	6.82	43.21	26.08	2.57	2.50
910.10	940.10	7.15	42.23	25.62	2.93	2.53
1010.10	1040.10	6.99	41.42	24.53	3.06	2.61
1110.10	1140.10	7.06	41.53	23.09	3.14	2.71
1210.10	1240.10	7.04	42.18	21.68	3.06	2.79
1310.10	1340.10	6.98	43.21	20.26	2.92	2.86
1410.10	1440.10	6.98	44.92	18.56	2.78	2.93
1510.10	1540.10	6.94	45.94	16.81	2.61	2.98



For detailed performance specs
& shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test procedures and are subject to change without notice. 3. The parts covered by this specification sheet are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and properties thereunder, please visit www.minicircuits.com/MCIStore/terms.jsp.

REV. OR
M109914
TUF-R5SM+
ED-12916/4
DJ/TD/AM
130502
Page 1 of 2

