

Surface Mount Frequency Mixer

Level 7 (LO Power +7dBm) 5 to 1000 MHz

LRMS-2+
LRMS-2




Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
RF Power	50mW
IF Current	40mA
Permanent damage may occur if any of these limits are exceeded.	


Pin Connections

LO	1
RF	4
IF	5
GROUND	2,3,6

Outline Drawing



PCB Land Pattern




Outline Dimensions (inch)

A	B	C	D	E	F	G
.400	.31	.200	.10	.010	.100	.050
10.16	7.87	5.08	2.54	0.25	2.54	1.27

H	J	K	L	M	wt
.420	.120	.060	.100	.020	grams
10.67	3.05	1.52	2.54	0.51	0.55

Demo Board MCL P/N: TB-44+ Suggested PCB Layout (PL-083)



- NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS 0.030" ± 0.002"; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
3. DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
4. DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

Features

- low conversion loss, 6.67 dB typ.
- excellent L-R isolation, 40 dB typ.

Applications

- VHF/UHF
- instrumentation
- cellular

CASE STYLE: QQQ130
PRICE: \$6.95 ea. QTY (1-9)

+ RoHS compliant in accordance
with EU Directive (2002/95/EC)

The +Suffix identifies RoHS Compliance. See our web site
for RoHS Compliance methodologies and qualifications.

Electrical Specifications

FREQUENCY (MHz)		CONVERSION LOSS (dB)				LO-RF ISOLATION (dB)						LO-IF ISOLATION (dB)						IP3 at center band (dBm)
LO/RF f_L - f_U	IF	Mid-Band m		Total Range		L	M	U	L	M	U	L	M	U				
		$\bar{X}$	σ	Max.	Max.													
		Typ.	Min.	Typ.	Min.										Typ.	Min.	Typ.	
5-1000	DC-1000	6.67	.26	8.0	9.5	60	40	40	20	25	18	55	30	30	20	20	12	16

1 dB COMP.: +1 dBm typ.


L = low range [f_L to 10 f_L]
m= mid band [$2f_L$ to $f_U/2$]

M = mid range [10 f_L to $f_U/2$]
U = upper range [$f_U/2$ to f_U]

Typical Performance Data

Frequency (MHz)		Conversion Loss (dB)	Isolation L-R (dB)	Isolation L-I (dB)	VSWR RF Port (:1)	VSWR LO Port (:1)
RF	LO	LO +7dBm	LO +7dBm	LO +7dBm	LO +7dBm	LO +7dBm
5.00	35.00	7.10	54.80	61.28	1.65	2.68
10.00	40.00	6.75	53.66	60.10	1.39	2.70
34.00	64.00	6.65	49.48	56.02	1.28	2.69
42.00	72.00	6.71	48.42	54.85	1.29	2.68
50.00	80.00	6.65	47.48	53.84	1.30	2.65
75.00	105.00	6.64	45.18	51.63	1.31	2.61
100.00	130.00	6.75	43.57	50.79	1.31	2.68
200.00	230.00	6.76	38.78	47.49	1.32	2.76
250.00	280.00	6.77	37.05	44.64	1.34	2.60
300.00	330.00	6.83	35.93	42.49	1.32	2.72
400.00	430.00	6.97	34.39	38.85	1.30	2.70
450.00	480.00	6.93	33.35	36.67	1.30	2.67
500.00	530.00	7.05	32.80	35.07	1.29	2.83
550.00	580.00	7.12	31.89	32.96	1.29	2.91
600.00	630.00	7.08	31.55	31.69	1.29	2.60
700.00	730.00	7.06	30.41	29.33	1.26	2.90
750.00	780.00	7.16	29.49	27.72	1.31	2.89
800.00	830.00	7.08	28.87	26.26	1.38	3.38
900.00	930.00	6.95	27.66	22.68	1.65	3.59
1000.00	1030.00	7.11	27.40	21.43	1.80	3.96

Electrical Schematic



Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED

For detailed performance specs
& shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com







IF/RF MICROWAVE COMPONENTS

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp.

REV. B
M102713
LRMS-2
DJ/FL/CP/AM
070521
Page 1 of 2

Performance Charts

LRMS-2+ LRMS-2



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine  Provides ACTUAL Data Instantly at minicircuits.com

IF/RF MICROWAVE COMPONENTS

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.