


Ceramic

Frequency Mixer WIDE BAND

Level 10 (LO Power+10 dBm) 2800 to 8000 MHz

MCA1T-80LH+



Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-40°C to 85°C
RF Power	50 mW
IF Current	40 mA
Permanent damage may occur if any of these limits are exceeded.	

Pin Connections

LO	10
RF	5
IF	3
GROUND	1,2,4,6,7,8,9

Features

- wide bandwidth, 2800 to 8000 MHz
- low conversion loss, 5.9 dB typ.
- high L-R isolation, 35 dB typ.
- IF, DC to 1250 MHz
- LTCC double balanced mixer
- aqueous washable
- low cost
- low profile, 0.095"
- protected by US Patent 7,027,795
- additional patent pending

Applications

- satellite up and down converters
- line of sight links
- defense radar
- defense communication


CASE STYLE: DZ885-2

PRICE: \$8.45 ea. QTY (10-49)

+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix has been added in order to identify RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.


Outline Drawing



Outline Dimensions (inch)

A	B	C	E	F	G
.350	.280	.095	.075	.050	.030
8.89	7.11	2.41	1.91	1.27	0.76
H	K	L	M	wt	
.074	.096	.321	.030	grams	
1.88	2.44	8.15	0.76	0.21	

Demo Board MCL P/N: TB-493+ Suggested PCB Layout (PL-288)



Electrical Specifications (T_{AMB}=-40°C to 85°C)

FREQUENCY (MHz)		CONVERSION LOSS (dB)			LO-RF ISOLATION (dB)		LO-IF ISOLATION (dB)		IP3 at center band (dBm)
LO/RF f _L -f _U	IF	$\bar{X}$	σ	Max.	Typ.	Min.	Typ.	Min.	
2800-8000	DC-1250	6.0	0.2	8.4*	35	25	13	8	15
2800-5000	DC-1250								
5000-8000	DC-1250	5.7	0.2	8.2*	35	20	40	19	12


1 dB COMPR. +5 dBm typ.

* Conversion loss at 30 MHz IF, increases with IF frequency.

Typical Performance Data

Frequency (MHz)		Conversion Loss (dB)	Isolation L-R (dB)	Isolation L-I (dB)	VSWR RF Port (:1)	VSWR LO Port (:1)
RF	LO	LO +10dBm	LO +10dBm	LO +10dBm	LO +10dBm	LO +10dBm
2800.00	2830.10	6.01	38.69	10.54	2.56	2.86
3106.00	3136.10	5.29	41.71	12.00	2.28	2.83
3406.00	3436.10	4.98	40.03	13.45	1.68	2.69
3706.00	3736.10	4.91	29.58	13.53	1.45	2.58
4000.00	4030.10	5.72	31.08	13.04	1.96	2.56
4300.00	4330.10	6.77	28.29	15.90	1.99	2.60
4600.00	4630.10	6.42	29.67	20.20	1.70	2.57
4900.00	4930.10	6.53	41.70	23.73	2.24	2.35
5200.00	5230.10	5.64	41.08	26.38	2.00	2.36
5500.00	5530.10	5.70	42.50	28.95	1.84	2.20
5800.00	5830.10	5.77	50.71	32.43	2.05	2.18
6100.00	6130.10	6.17	40.53	35.90	2.78	2.43
6400.00	6430.10	5.77	37.72	39.36	2.50	2.32
6700.00	6730.10	5.66	33.56	43.31	2.41	2.48
7000.00	7030.10	5.55	31.26	41.62	2.28	2.56
7300.00	7330.10	5.66	31.10	37.52	2.24	2.48
7600.00	7630.10	5.85	28.60	30.61	2.18	2.54
7800.00	7830.10	5.79	28.27	23.94	1.96	2.43
7900.00	7930.10	5.83	27.62	20.54	1.79	2.41
8000.00	8030.10	5.80	25.80	19.33	1.60	2.52

Electrical Schematic



Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED

IF/RF MICROWAVE COMPONENTS

For detailed performance specs & shopping online see web site









P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

REV. A
M128524
MCA1-80LH+
DJ/RS/CP/AM
100816
Page 1 of 2

Performance Charts

MCA1T-80LH+



Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

IF/RF MICROWAVE COMPONENTS

For detailed performance specs
& shopping online see web site

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.