

Surface Mount Frequency Mixer

RMS-1LH+ RMS-1LH

Level 10 (LO Power +10 dBm) 2 to 500 MHz




Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
RF Power	50mW
IF Current	40mA
Permanent damage may occur if any of these limits are exceeded.	

Pin Connections

LO	1
RF	4
IF	5
GROUND	2,3,6


Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F
.250	.31	.20	.100	.050	.055
6.35	7.87	5.08	2.54	1.27	1.40
G	H	J	K	wt	
.040	.070	.270	.050	grams	
1.02	1.78	6.86	1.27	0.50	

Demo Board MCL P/N: TB-03 Suggested PCB Layout (PL-052)



Features

- excellent L-R isolation, 44 dB typ.
- conversion loss, 5.68 dB typ.
- small size, 0.25"x0.31"x0.2"

Applications

- HF & VHF communications
- intermediate frequency for down converters

CASE STYLE: TT240

PRICE: \$7.95 ea. QTY (1-9)

+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.

Electrical Specifications

FREQUENCY (MHz)	CONVERSION LOSS (dB)	LO-RF ISOLATION (dB)			LO-IF ISOLATION (dB)			IP3 at center band (dBm)
		L	M	U	L	M	U	
$f_c - f_u$	\bar{X} σ Max. Total Range Max.	Typ. Min.	Typ. Min.	Typ. Min.	Typ. Min.	Typ. Min.	Typ. Min.	Typ.
2-500 DC-500	5.68 0.11 7.0 8.0	58 45	44 25	30 20	55 40	40 25	28 17	15


1 dB COMP.: +5 dBm typ.
For phase detection, DC output positive with in-phase RF & LO.

L = low range [f_l to $10 f_l$]
M = mid range [$10 f_l$ to $f_u/2$]
U = upper range [$f_u/2$ to f_u]

Typical Performance Data

Frequency (MHz)		Conversion Loss (dB)	Isolation L-R (dB)	Isolation L-I (dB)	VSWR RF Port (:1)	VSWR LO Port (:1)
RF	LO	LO +10dBm	LO +10dBm	LO +10dBm	LO +10dBm	LO +10dBm
10.10	40.10	5.60	74.28	45.84	1.06	2.46
49.80	79.80	5.69	60.16	43.26	1.04	2.50
89.50	119.50	5.68	55.26	41.54	1.05	2.36
129.20	159.20	5.75	52.39	40.39	1.06	2.46
168.90	198.90	5.77	50.72	39.56	1.07	2.38
208.60	238.60	5.78	49.03	38.78	1.09	2.45
248.30	278.30	5.86	48.01	37.59	1.09	2.47
287.90	317.90	5.87	46.41	36.30	1.10	2.47
327.60	357.60	5.93	45.92	34.99	1.10	2.57
367.30	397.30	5.98	44.83	33.07	1.10	2.54
407.00	437.00	5.98	42.83	31.78	1.12	2.62
446.70	476.70	6.02	41.37	31.24	1.13	2.66
486.40	516.40	6.07	40.02	30.07	1.14	2.69
526.10	556.10	6.14	38.49	29.39	1.14	2.78
565.80	595.80	6.18	37.45	27.46	1.15	2.79

Electrical Schematic



Mini-Circuits
ISO 9001 ISO 14001 AS 9100 CERTIFIED

For detailed performance specs & shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

IF/RF MICROWAVE COMPONENTS

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuits' applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

REV. B
M111026
RMS-1LH
070419
Page 1 of 2

Performance Charts

