


Surface Mount Frequency Mixer

Level 17 (LO Power +17 dBm) 50 to 1000 MHz

SYM-10DHW+ SYM-10DHW



CASE STYLE: TTT167
PRICE: \$16.95 ea. QTY (1-9)

+ RoHS compliant in accordance
with EU Directive (2002/95/EC)

The +Suffix identifies RoHS Compliance. See our web site
for RoHS Compliance methodologies and qualifications.

Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
RF Power	200mW
IF Current	40mA

Permanent damage may occur if any of these limits are exceeded.

Pin Connections

LO	2
RF	1
IF	3
GROUND	4,5,6


Features

- low conversion loss, 7.0 dB typ.
- excellent L-R isolation, 48 dB typ.
- high IP3, 25 dBm typ.

Applications

- UHF TV
- cellular
- ISM/GSM


Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H	J	K
.38	.50	.23	.020	.075	.250	.425	.187	.050	.050
9.65	12.70	5.84	0.51	1.91	6.35	10.80	4.75	1.27	1.27
L	M	N	P	Q	R	S	T	wt.	
.070	.270	.540	.060	.095	.445	.208	.415	grams	
1.78	6.86	13.72	1.52	2.41	11.30	5.28	10.54		0.8

Demo Board MCL P/N: TB-12
Suggested PCB Layout (PL-079)



Electrical Specifications


FREQUENCY (MHz)		CONVERSION LOSS (dB)			LO-RF ISOLATION (dB)		LO-IF ISOLATION (dB)		IP3 at center band (dBm)
LO/RF	IF	Mid-Band	Total Range	Max.	Max.	Typ.	Min.	Typ.	Min.
$f_L - f_U$	\bar{X}	m	Max.						
50-1000	20-800	7.0	8.5	9.8	45	30	29	20	25

1 dB COMP: +14 dBm typ.
m= mid band [$2f_L$ to $f_U/2$]

Typical Performance Data

Frequency (MHz)		Conversion Loss (dB)	Isolation L-R (dB)	Isolation L-I (dB)	VSWR RF Port (:1)	VSWR LO Port (:1)
RF	LO	LO +17dBm	LO +17dBm	LO +17dBm	LO +17dBm	LO +17dBm
50.00	80.00	6.80	49.30	41.30	1.51	1.53
80.00	110.00	6.60	50.20	41.70	1.54	1.48
100.00	130.00	6.69	49.80	42.20	1.51	1.54
117.86	147.86	6.68	48.50	41.80	1.52	1.59
185.71	215.71	6.81	45.70	41.10	1.57	1.53
253.57	283.57	6.92	43.50	39.90	1.53	1.50
300.00	330.00	6.95	42.70	38.60	1.48	1.65
321.43	351.43	6.86	42.20	37.70	1.47	1.56
389.29	419.29	7.14	43.10	36.90	1.46	1.65
457.14	487.14	7.15	42.20	34.70	1.38	1.43
500.00	530.00	7.03	43.60	33.10	1.35	1.41
525.00	555.00	7.03	47.50	32.20	1.34	1.30
592.86	622.86	7.15	51.40	29.00	1.33	1.34
660.71	690.71	7.14	43.40	27.50	1.28	1.39
728.57	758.57	7.14	40.00	27.10	1.29	1.37
796.43	826.43	7.39	40.90	27.50	1.34	1.40
800.00	830.00	7.44	41.00	27.60	1.34	1.41
864.29	894.29	7.53	43.60	26.70	1.36	1.46
932.14	962.14	7.93	41.70	25.90	1.46	1.48
1000.00	1030.00	8.38	37.10	25.20	1.61	1.44

Electrical Schematic



Mini-Circuits
ISO 9001 ISO 14001 AS 9100 CERTIFIED

For detailed performance specs
& shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

IF/RF MICROWAVE COMPONENTS

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp.

REV. E
M112207
SYM-10DHW
ED-6487/2
DJ/TD/AM
091006
Page 1 of 2

Performance Charts

