

Coaxial Frequency Mixer

Level 10 (LO Power +10 dBm) 20 to 1500 MHz

ZP-5LH+
ZP-5LH



Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
RF Power	50mW
IF Current	40mA

Permanent damage may occur if any of these limits are exceeded.

Coaxial Connections

LO	L
RF	R
IF	X

Features

- low conversion loss, 6.9 dB typ.
- excellent L-R isolation, 42 dB typ.
- wideband, 20 to 1500 MHz
- rugged shielded case

Applications

- VHF/UHF
- satellite distribution
- instrumentation


BNC version shown
CASE STYLE: GG60

Connectors	Model	Price	Qty.
BNC	ZP-5LH-(+)	\$45.95 ea.	(1-9)
SMA	ZP-5LH-S+	\$50.95 ea.	(1-9)

+ RoHS compliant in accordance
with EU Directive (2002/95/EC)

The +Suffix identifies RoHS Compliance. See our web site
for RoHS Compliance methodologies and qualifications.

Outline Drawing



Outline Dimensions (inch)

A	B	C	D	E	F	G	H	wt
2.31	1.20	.60	.125	2.062	.30	.53	.63	grams
58.67	30.48	15.24	3.18	52.37	7.62	13.46	16.00	75.0

Electrical Specifications

FREQUENCY (MHz)		CONVERSION LOSS (dB)				LO-RF ISOLATION (dB)						LO-IF ISOLATION (dB)					
LO/RF f_L - f_U	IF	Mid-Band m		Total Range		L		M		U		L		M		U	
		$\bar{X}$	σ	Max.	Max.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.
20-1500	DC-1000	6.9	0.27	8.5	9.0	53	40	42	30	38	25	40	25	30	18	22	8


1 dB COMP.: +5 dBm typ.

L = low range [f_L to $10 f_L$] M = mid range [$10 f_L$ to $f_U/2$] U = upper range [$f_U/2$ to f_U]
m = mid band [$2f_L$ to $f_U/2$]

Typical Performance Data

Frequency (MHz)		Conversion Loss (dB)	Isolation L-R (dB)	Isolation L-I (dB)	VSWR RF Port (:1)	VSWR LO Port (:1)
RF	LO	LO +10dBm	LO +10dBm	LO +10dBm	LO +10dBm	LO +10dBm
20.00	50.00	5.60	62.84	53.91	1.43	2.57
50.00	80.00	5.38	57.81	46.30	1.32	2.51
100.00	70.00	5.25	52.60	40.86	1.31	2.50
158.75	128.75	5.20	49.11	38.29	1.34	2.38
200.00	170.00	5.25	47.45	36.98	1.48	2.28
297.50	267.50	5.37	44.43	34.13	1.59	2.36
436.25	406.25	5.54	42.14	31.89	1.91	2.34
500.00	470.00	5.74	41.47	30.68	2.36	2.36
575.00	545.00	5.89	40.90	30.02	2.49	2.36
713.75	683.75	6.61	40.16	28.61	2.97	2.45
750.00	720.00	6.80	39.71	28.48	3.40	2.46
760.00	730.00	6.83	39.62	28.42	3.53	2.48
852.50	822.50	7.07	39.30	28.00	3.80	2.56
991.25	961.25	6.99	38.97	26.26	3.86	2.67
1000.00	970.00	7.07	38.98	26.16	3.95	2.70
1130.00	1100.00	7.19	35.93	24.11	3.91	2.73
1222.50	1192.50	7.02	38.98	22.14	3.77	2.73
1361.25	1331.25	6.88	39.21	19.23	3.65	2.77
1453.75	1423.75	6.78	38.09	16.51	3.54	2.78
1500.00	1470.00	6.66	37.95	16.08	3.47	2.77

Electrical Schematic



Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

IF/RF MICROWAVE COMPONENTS







Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuit's standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuit's website at www.minicircuits.com/MCLStore/terms.jsp.

For detailed performance specs
& shopping online see web site

REV. A
M98898
ZP-5LH
DJ/TD/CP/AM
100205
Page 1 of 2

Performance Charts

ZP-5LH+
ZP-5LH



Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine  Provides ACTUAL Data Instantly at minicircuits.com

IF/RF MICROWAVE COMPONENTS

For detailed performance specs
& shopping online see web site

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.