

Coaxial Frequency Mixer

Level 17 (LO Power +17 dBm) 5 to 1200 MHz

ZFM-4H+
ZFM-4H



SMA version shown

CASE STYLE: K18

Connectors	Model	Price	Qty.
BNC	ZFM-4H(+)	\$73.95 ea.	(1-9)
SMA	ZFM-4H-S+	\$78.95 ea.	(1-9)
BRACKET (OPTION "B")		\$5.00	(1+)

+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.

Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
RF Power	200mW
IF Current	40mA

Permanent damage may occur if any of these limits are exceeded.

Coaxial Connections

LO	1
RF	2
IF	3

Features

- low conversion loss, 4.97 dB typ.
- good L-R isolation, 35 dB typ, L-I, 35 dB typ.
- wideband, 5 to 1200 MHz
- rugged shielded case

Applications

- VHF/UHF
- cellular
- instrumentation
- GPS
- federal & defense communications

Electrical Specifications

FREQUENCY (MHz)		CONVERSION LOSS (dB)				LO-RF ISOLATION (dB)						LO-IF ISOLATION (dB)					
LO/RF	IF	Mid-Band		Total		L		M		U		L		M		U	
f_L-f_U		$\bar{X}$	σ	Max.	Max.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.	Typ.	Min.
5-1200	DC-1200	6.59	0.03	8.0	9.0	50	40	35	25	30	20	50	40	35	20	30	20

1 dB COMP.: +14 dBm typ.

For phase detection: DC output has positive with in-phase LO and RF signals


L = low range [f_L to $10 f_L$] M = mid range [$10 f_L$ to $f_U/2$] U = upper range [$f_U/2$ to f_U]

m = mid band [$2f_L$ to $f_U/2$]

Typical Performance Data

Frequency (MHz)		Conversion Loss (dB)	Isolation L-R (dB)	Isolation L-I (dB)	VSWR RF Port (:1)	VSWR LO Port (:1)
RF	LO	LO +17dBm	LO +17dBm	LO +17dBm	LO +17dBm	LO +17dBm
10.1	40.1	7.31	68.49	65.02	1.44	1.65
30.1	60.1	7.41	62.74	61.70	1.48	1.58
70.1	100.1	7.27	58.08	57.43	1.53	1.52
130.1	160.1	7.26	54.30	54.15	1.46	1.56
210.1	240.1	7.09	50.37	51.33	1.49	1.57
270.1	300.1	6.90	48.42	49.71	1.51	1.54
330.1	360.1	6.95	46.73	48.36	1.48	1.56
390.1	420.1	6.72	45.73	46.94	1.45	1.58
470.1	500.1	6.58	44.28	44.09	1.41	1.62
570.1	600.1	6.71	43.16	42.65	1.41	1.68
650.1	680.1	6.76	42.76	41.88	1.38	1.74
710.1	740.1	6.88	42.70	41.40	1.34	1.80
770.1	800.1	6.86	42.34	40.92	1.32	1.83
830.1	860.1	7.03	41.64	40.87	1.33	1.85
890.1	920.1	7.28	40.53	40.72	1.34	1.88
950.1	980.1	7.44	39.87	40.58	1.40	1.91
1010.1	1040.1	7.57	39.31	41.31	1.44	1.95
1090.1	1120.1	7.55	38.73	41.13	1.47	2.01
1170.1	1200.1	7.88	37.96	41.66	1.57	2.10
1210.1	1240.1	8.21	37.28	41.74	1.65	2.11

Outline Drawing




Outline Dimensions (inch)

A	B	C	D	E	F	G	H
1.25	1.25	.75	.63	.38	1.00	.125	1.000
31.75	31.75	19.05	16.00	9.65	25.40	3.18	25.40

J	K	L	M	N	P	Q	wt
--	--	.125	1.688	2.18	.75	.07	grams
--	--	3.18	42.88	55.37	19.05	1.78	70.0

Electrical Schematic



Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

IF/RF MICROWAVE COMPONENTS







For detailed performance specs & shopping online see web site

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

REV. C
M110671
ZFM-4H
DJ/TD/CP
120306
Page 1 of 2

Performance Charts

**ZFM-4H+
ZFM-4H**



P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine www.minicircuits.com Provides ACTUAL Data Instantly at [minicircuits.com](http://www.minicircuits.com)

IF/RF MICROWAVE COMPONENTS

For detailed performance specs
& shopping online see web site

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.