

Coaxial

Frequency Mixer WIDE BAND

ZX05-43H+

Level 17 (LO Power +17 dBm) 1000 to 4000 MHz



Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
RF Power	100mW

Permanent damage may occur if any of these limits are exceeded.

Coaxial Connections

LO	2
RF	3
IF	1

Features

- wide bandwidth, 1000 to 4000 MHz, useable down to 800 MHz
- low conversion loss, 6.1 dB typ.
- excellent L-R isolation, 35 dB typ.
- rugged construction
- small size
- useable as up and down converter
- protected by US patents, 6,790,049 and 7,027,795

Applications

- cellular
- defense and weather radar
- defense communications
- PCN
- WCDMA
- WIFI
- blue tooth
- VSAT
- ISM


CASE STYLE: FL905

Connectors	Model	Price	Qty.
SMA	ZX05-43H-S+	\$46.95	(1-24)

+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix has been added in order to identify RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.

Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F	G
.74	.90	.54	.50	.04	.16	.29
18.80	22.86	13.72	12.70	1.02	4.06	7.37

H	J	K	L	M	N	wt
.37	--	.122	.496	.106	.122	grams
9.40	--	3.10	12.60	2.69	3.10	20.0

Electrical Specifications

FREQUENCY (MHz)	CONVERSION LOSS* (dB)	LO-RF ISOLATION (dB)		LO-IF ISOLATION (dB)		IP3 at center band (dBm)	
		Typ.	Min.	Typ.	Min.		
LO/RF f _L -f _u	IF	Typ.	σ	Max.	Typ.	Min.	Typ.
1000-4000	DC-1500						
1000-2500		6.5	0.1	9.3	37	32	22
2500-4000		6.0	0.1	9.6	31	25	22


1 dB COMPR.: +14 dBm typ.

* Conversion loss at 30 MHz IF. σ is a measure of repeatability from unit to unit.

Typical Performance Data

Frequency (MHz)	Conversion Loss (dB)	Isolation L-R (dB)	Isolation L-I (dB)	VSWR RF Port (:1)	VSWR LO Port (:1)	
					LO +17dBm	LO +17dBm
RF	LO	LO +17dBm	LO +17dBm	LO +17dBm	LO +17dBm	LO +17dBm
1000.10	1030.10	7.95	37.91	24.63	2.64	1.90
1200.10	1230.10	6.57	43.66	28.59	3.37	1.42
1400.10	1430.10	6.28	38.32	31.65	3.61	2.05
1600.10	1630.10	6.57	36.58	25.15	3.63	2.17
1800.10	1830.10	6.89	37.44	17.66	3.90	1.85
2000.10	2030.10	7.00	36.67	10.13	3.84	1.26
2200.10	2230.10	6.97	39.95	9.74	3.90	1.50
2400.10	2430.10	6.36	37.84	12.34	2.96	2.34
2500.10	2530.10	7.89	42.17	13.94	3.97	2.62
2600.10	2630.10	8.97	38.42	15.44	4.32	2.72
2700.10	2730.10	7.12	37.70	16.93	3.29	2.70
2800.10	2830.10	6.62	35.31	18.55	2.39	2.73
2900.10	2930.10	5.86	39.36	20.26	1.80	2.86
3000.10	3030.10	5.50	35.81	23.07	1.35	2.91
3100.10	3130.10	5.24	32.82	25.94	1.19	2.57
3200.10	3230.10	5.25	31.48	27.83	1.19	2.19
3400.10	3430.10	5.69	30.99	23.88	1.28	1.61
3600.10	3630.10	6.16	27.70	21.27	1.92	1.67
3800.10	3830.10	6.60	27.93	18.12	2.65	2.30
4000.10	4030.10	7.95	29.47	19.70	3.90	3.89

Electrical Schematic



Mini-Circuits
ISO 9001 ISO 14001 AS 9100 CERTIFIED

For detailed performance specs & shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine www.minicircuits.com Provides ACTUAL Data Instantly at minicircuits.com

IF/RF MICROWAVE COMPONENTS

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

REV. OR
M111660
ZX05-43H+
ED-12902/12
DJ/TD/QL
091007
Page 1 of 2

