


X2 Frequency Multiplier

50Ω Output 140 to 3000 MHz

FK-3000+



CASE STYLE: H16

Connectors	Model	Price	Qty.
SMA	FK-3000+	\$79.95	(1-9)
BRACKET (OPTION "B")		\$5.00	(1+)

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
RF Input Power	200mW

Permanent damage may occur if any of these limits are exceeded.

Features


- wideband, 140 to 3000 MHz
- low insertion loss, 11 dB typ.
- rugged shielded case

Applications

- synthesizers
- local oscillators

Outline Drawing

STANDARD



Outline Dimensions (inch)

A	B	C	D	E	F	G	H	J	K	L	M	N	P	Q	wt
1.25	1.25	.75	.63	.38	1.000	.125	1.000	--	--	.125	1.688	2.18	.750	.06	grams
31.75	31.75	19.05	16.00	9.65	25.40	3.18	25.40	--	--	3.18	42.88	55.37	19.05	1.52	70.0





Electrical Specifications

MULTIPLICATION FACTOR	FREQUENCY (MHz)		INPUT POWER (dBm)		CONVERSION LOSS (dB)		*HARMONIC OUTPUT (dBc)					
	F1 Input	F2 Output	Min.	Max.	Typ.	Max.	F1		F3		F4	
2	70-1000	140-2000	12	15	11.0	14.0	31	20	40	25	15	10
	1000-1500	2000-3000	12	15	12.0	17.5	22	15	30	20	30	14

* Harmonics of input frequency below the power level of F2

Typical Performance Data

Input Frequency (MHz)	Conversion Loss (dB) F2	Harmonic Output (-dBc)			
		F1	F3	F4	
70.00	10.32	49.20	51.20	15.70	
100.00	10.54	50.60	54.20	15.60	
200.00	10.39	43.70	54.10	16.90	
450.00	10.94	34.30	46.80	15.60	
500.00	10.91	34.80	47.80	14.90	
700.00	10.69	29.70	43.40	16.90	
900.00	10.56	28.10	39.50	23.10	
1000.00	10.82	25.80	33.90	21.70	
1200.00	12.43	25.10	42.90	25.60	
1500.00	13.30	21.90	29.70	40.20	



Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

