

50Ω

137 to 143 MHz

Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
LO/RF Power	50mW
I&Q Current	40mA
Permanent damage may occur if any of these limits are exceeded.	

Pin Connections

LO (carrier)	13
RF (signal)	1
I (0°)(ref.)	8
Q (90°)*	5
ISOLATE**	10,11
GROUND	2,3,4,6,7,9,12,14,15,16

* Q=I +90° for LO<RF

Q=I -90° for LO>RF

**external variable capacitors can be connected at pins 10&11 to ground for improvement of phase unbalance.

Features

- good amplitude and phase unbalance
- excellent 3rd and 5th harmonic suppression

Applications

- radar
- communication systems



CASE STYLE: C07

PRICE: \$22.20 ea. QTY (1-49)

Demodulator Electrical Specifications

MODEL NO.	FREQUENCY (MHz)				CONVERSION LOSS (dB)			AMPLITUDE UNBALANCE (dB)		PHASE UNBALANCE (Deg.)		HARMONIC SUPPRESSION (dBc)			
	RF (SIGNAL)	LO (CARRIER)	I&Q		$\bar{x}$	σ	Max.	Typ.	Max.	with reference to 90°		3XI/Q	5XI/Q		
MIQY-140D	f _L	f _U	Min.	Max.						Typ.	Max.	Typ.	Min.	Typ.	Min.
	137	143	DC	5	5.5	0.25	7.0	0.10	0.6	0.5	3.0	47	35	70	50

Note:

1. Operating LO Power: 10±0.5 dBm

2. 1 dB Compression at +4 dBm RF input


3. DC offset 1mV typ.

4. Conversion Loss=RF power, dBm - (I+Q) power, dBm

Typical Performance Data



Frequency (MHz)		Conversion Loss (dB)	Amplitude Unbalance (dB)	Phase (I&Q) (deg.)	Frequency (MHz)		DC Offset (mV)
RF	I&Q				LO	RF	
140.10	0.30	5.52	0.05	89.79	137.00	137.10	-0.08
140.48	0.66	5.50	0.05	89.81	137.46	137.56	-0.16
140.85	1.03	5.49	0.06	89.93	137.92	138.02	-0.06
140.98	1.15	5.49	0.10	89.99	138.08	138.18	-0.13
141.23	1.38	5.49	0.08	90.09	138.39	138.49	-0.13
141.61	1.75	5.50	0.06	89.96	138.85	138.95	-0.19
141.86	1.99	5.50	0.04	89.97	139.15	139.25	-0.14
141.99	2.11	5.50	0.06	90.00	139.31	139.41	-0.08
142.36	2.47	5.50	0.10	90.17	139.77	139.87	-0.07
142.74	2.83	5.50	0.11	90.19	140.23	140.33	-0.07
142.86	2.96	5.51	0.07	90.04	140.39	140.49	-0.11
143.12	3.19	5.51	0.08	90.14	140.69	140.79	-0.18
143.49	3.56	5.51	0.12	90.22	141.15	141.25	-0.17
143.74	3.79	5.51	0.08	89.94	141.46	141.56	-0.14
143.87	3.92	5.51	0.13	90.00	141.62	141.72	-0.19

Outline Drawing




Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H	wt
.770	.810	.380	.410	.030	.200	.20	.14	grams
19.56	20.57	9.65	10.41	0.76	5.08	5.08	3.56	11.0

MIQY-140D
AMPLITUDE & PHASE UNBALANCEMIQY-140D
DC OFFSET

I&Q demodulation block diagram



Notes

- Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
- Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
- The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp