

Voltage Controlled Oscillator

ROS-310-419+

Wide Band 160 to 360 MHz

Features

- very wide band frequency
- low phase noise
- low pulling
- low pushing



CASE STYLE: CK605

PRICE: \$ 24.95 ea. QTY (5-49)

Applications

- wireline broadband access
- digital TV

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Electrical Specifications

MODEL NO.	FREQ. (MHz)		POWER OUTPUT (dBm)	PHASE NOISE dBc/Hz SSB at offset frequencies,kHz				TUNING					NON HARMONIC SPURIOUS (dBc)	HARMONICS (dBc)		PULLING pk-pk @ 12 dB _r (MHz)	PUSHING (MHz/V)	DC OPERATING POWER				
	Min.	Max.		Typ.	1	10	100	1000	VOLTAGE SENSITIVITY (V)		PORT CAP (pF)	3 dB MODULATION BANDWIDTH (MHz)		Typ.	Typ.			Max.	Typ.	Max.	V _{cc} (volts)	Current (mA)
									Range	Typ.												
ROS-310-419+	160	360	+7.5	-80	-102	-123	-144	0.5	18	9-18	230	1.7	-90	-28	-19	0.3	0.4	10	21			

Pin Connections

RF OUT	10
VCC	14
V-TUNE	2
GROUND	1,3,4,5,6,7,8,9,11,12,13,15,16


Maximum Ratings

Operating Temperature	-55°C to 85°C
Storage Temperature	-55°C to 100°C
Absolute Max. Supply Voltage (Vcc)	12V
Absolute Max. Tuning Voltage (Vtune)	20V
All specifications	50 ohm system


Permanent damage may occur if any of these limits are exceeded.

Outline Drawing

PCB Land Pattern



Demo Board MCL P/N: TB-10
Suggested PCB Layout (PL-012)



NOTES:

1. TRACE WIDTH IS SHOWN FOR FR4 WITH DIELECTRIC THICKNESS .030" $\pm$.002"; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
 2. BOTTOM SIDE OF THE BOTTOM IS CONTINUOUS GROUND PLANE.
- DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
- DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

Outline Dimensions ($\frac{\text{inch}}{\text{mm}}$)

A	B	C	D	E	F	G	H	J	K	L	M	N	P	Q	R	S	T	wt.
.500	.500	.180	.100	.080	.115	.060	.040	.540	.060	.100	.135	.135	.115	.140	.070	.150	.070	grams
12.70	12.70	4.57	2.54	2.03	2.92	1.52	1.02	13.72	1.52	2.54	3.43	3.43	2.92	3.56	1.78	3.81	1.78	1.0



For detailed performance specs
& shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine  Provides ACTUAL Data Instantly at minicircuits.com

REV. OR
M106250
EDR-7888
ROS-310-419+
RAV
120829
Page 1 of 2

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuits' applicable established industry standard performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCStore/terms_iso.

Performance Data & Curves*

ROS-310-419+

V TUNE	TUNE SENS (MHz/V)	FREQUENCY (MHz)			POWER OUTPUT (dBm)			Icc (mA)	HARMONICS (dBc)			FREQ. PUSH (MHz/V)	FREQ. PULL (MHz)	PHASE NOISE (dBc/Hz) at offsets				FREQ OFFSET (KHz)	PHASE NOISE at 260 MHz (dBc/Hz)
		-55°C	+25°C	+85°C	-55°C	+25°C	+85°C		F2	F3	F4			1kHz	10kHz	100kHz	1MHz		
0.00	17.67	143.5	140.9	139.2	6.45	6.15	5.56	16.61	-19.1	-36.9	-38.4	0.03	0.02	-79.3	-100.4	-123.2	-143.5	1.0	-80.91
0.50	16.13	152.0	149.8	148.3	7.13	7.29	7.00	16.82	-22.8	-41.0	-40.6	0.25	0.02	-79.1	-101.3	-125.1	-146.1	2.0	-86.55
1.00	15.07	160.0	157.8	156.4	7.41	7.63	7.41	16.83	-29.2	-48.5	-41.0	0.24	0.05	-81.1	-102.1	-124.8	-145.5	3.5	-93.16
2.00	15.46	175.2	172.8	171.3	7.70	7.99	7.80	16.77	-32.8	-44.4	-40.5	0.14	0.05	-80.6	-101.7	-124.8	-145.5	6.0	-97.32
3.00	16.16	191.0	188.5	186.7	7.74	8.11	7.92	16.63	-29.0	-42.2	-41.6	0.10	0.06	-82.1	-102.3	-125.0	-145.6	8.5	-101.57
4.00	16.22	207.6	205.2	203.2	7.67	8.09	7.97	16.48	-27.5	-39.4	-40.4	0.24	0.10	-80.4	-101.8	-123.8	-144.1	10.0	-101.20
5.00	17.48	224.6	222.0	220.4	7.71	8.03	7.86	16.20	-26.4	-38.3	-38.0	0.51	0.06	-80.6	-101.4	-123.1	-143.4	20.8	-109.53
6.00	18.00	242.1	239.4	237.8	7.57	7.93	7.75	15.95	-26.4	-38.0	-37.1	0.74	0.13	-80.9	-101.2	-122.9	-143.3	35.5	-114.91
7.00	15.71	259.9	256.7	254.4	7.38	7.88	7.76	15.76	-26.0	-38.0	-39.1	0.47	0.26	-80.9	-101.6	-125.2	-145.8	60.7	-120.60
8.00	16.28	276.3	273.3	271.4	7.08	7.75	7.68	15.50	-25.8	-35.5	-36.4	0.91	0.21	-79.9	-101.3	-124.0	-144.1	86.7	-124.21
9.00	12.48	291.9	288.6	285.9	7.14	7.76	7.44	15.33	-24.3	-37.6	-38.0	0.34	0.36	-79.1	-102.5	-125.9	-146.3	100.0	-125.49
10.00	14.55	305.2	302.2	300.3	6.36	7.06	7.05	15.10	-27.8	-35.6	-37.7	0.79	0.37	-78.1	-101.1	-124.9	-145.4	148.1	-129.16
11.00	12.62	319.1	316.2	314.1	6.36	7.06	7.12	14.98	-26.9	-36.1	-35.1	0.43	0.41	-78.3	-102.5	-125.0	-145.2	177.0	-131.02
12.00	10.73	331.1	328.4	326.1	6.38	7.10	7.12	14.86	-26.3	-36.9	-35.2	0.15	0.55	-80.7	-103.2	-124.9	-145.0	211.6	-132.44
13.00	10.60	341.5	338.8	336.6	6.09	6.81	6.74	14.75	-27.3	-37.2	-35.9	0.22	0.85	-78.9	-103.2	-125.5	-145.5	302.4	-135.86
14.00	10.59	352.5	349.6	347.6	5.83	6.49	6.53	14.67	-28.5	-37.0	-36.2	0.66	0.70	-79.7	-102.2	-125.5	-146.1	361.5	-137.42
15.00	9.35	362.9	359.9	357.7	5.79	6.43	6.49	14.61	-27.0	-37.6	-34.8	0.49	0.69	-77.0	-103.4	-125.4	-145.7	507.5	-140.39
16.00	8.24	371.9	368.9	366.7	5.72	6.37	6.43	14.57	-25.9	-39.0	-33.3	0.33	0.70	-78.1	-103.2	-125.1	-145.3	606.7	-141.96
17.00	7.27	379.9	376.9	374.7	5.60	6.26	6.32	14.53	-25.5	-40.5	-32.4	0.19	0.69	-80.0	-104.0	-124.8	-145.1	851.6	-144.81
18.00	6.37	386.8	384.0	381.7	5.44	6.10	6.13	14.49	-26.1	-42.6	-31.5	0.06	0.67	-80.1	-102.7	-124.3	-144.6	1000.0	-145.90

*at 25°C unless mentioned otherwise

