

Voltage Controlled Oscillator

SOS-915-119+

5V Tuning for PLL IC's 832 to 998 MHz

Features

- linear tuning characteristic
- small size 0.3" x 0.3"
- aqueous washable

Applications

- wireless communications
- base station



CASE STYLE: FZ802

PRICE: \$ 20.60 ea. QTY (5-49)

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Electrical Specifications

MODEL NO.	FREQ. (MHz)		POWER OUTPUT (dBm)	PHASE NOISE dBc/Hz SSB at offset frequencies,kHz				TUNING				NON HARMONIC SPURIOUS (dBc)	HARMONICS (dBc)		PULLING pk-pk @12 dBr (MHz)	PUSHING (MHz/V)	DC OPERATING POWER				
	Min.	Max.		1	10	100	1000	VOLTAGE RANGE (V)	SENSI- TIVITY (MHz/V)	PORT CAP (pF)	3 dB MODULATION BANDWIDTH (MHz)		Typ.	Typ.			Max.	Typ.	Typ.	Vcc (volts)	Current (mA)
SOS-915-119+	832	998	+5	-66	-91	-117	-137	0.5	4	100	10	110	-90	-19	-10	4	5	4	32		

Pin Connections


RF OUT	8
VCC	11
V-TUNE	1
GROUND	2,3,4,5,6,7,9,10,12

Maximum Ratings


Operating Temperature	-55°C to 85°C
Storage Temperature	-55°C to 100°C
Absolute Max. Supply Voltage (Vcc)	6V
Absolute Max. Tuning Voltage (Vtune)	6V
All specifications	50 ohm system

Permanent damage may occur if any of these limits are exceeded.

Outline Drawing



Demo Board MCL P/N: TB-271 Suggested PCB Layout (PL-143)



NOTE:

1. TRACE WIDTH IS SHOWN FOR FR4 WITH DIELECTRIC THICKNESS $.025 \pm 0.002$; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.

- DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
- DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

Outline Dimensions (inch mm)

A	B	C	D	E	F	G	H	J	K	L	M	N	P	Q	R	wt.
.300	.300	.070	.060	.120	.039	.075	.120	.030	.050	.340	.140	.340	.140	.050	.040	grams
7.62	7.62	1.78	1.52	3.05	0.99	1.91	3.05	0.76	1.27	8.64	3.56	8.64	3.56	1.27	1.02	.25

Performance Data & Curves*

SOS-915-119+

V TUNE	TUNE SENS (MHz/V)	FREQUENCY (MHz)			POWER OUTPUT (dBm)			Icc (mA)	HARMONICS (dBc)			FREQ. PUSH (MHz/V)	FREQ. PULL (MHz)	PHASE NOISE (dBc/Hz) at offsets				FREQ OFFSET (KHz)	PHASE NOISE at 915 MHz (dBc/Hz)
		-55°C	+25°C	+85°C	-55°C	+25°C	+85°C		F2	F3	F4			1kHz	10kHz	100kHz	1MHz		
0.00	129.21	709.8	681.3	665.3	5.03	5.41	5.30	25.06	-30.9	-17.9	-47.9	6.90	2.21	-67.8	-92.4	-115.0	-135.4	1.0	-66.67
0.25	116.48	740.8	713.6	699.4	5.25	5.53	5.35	25.16	-30.0	-17.4	-46.7	7.18	5.23	-66.6	-90.9	-114.8	-135.3	2.0	-74.05
0.50	110.20	769.0	742.7	730.2	5.33	5.61	5.36	25.23	-30.6	-17.0	-46.7	7.27	2.13	-66.9	-91.8	-114.7	-135.0	3.5	-81.44
0.75	105.57	795.9	770.2	758.9	5.39	5.56	5.27	25.25	-30.2	-16.9	-47.0	7.16	5.06	-66.4	-91.0	-114.3	-134.7	6.0	-84.79
1.00	101.99	821.5	796.6	786.6	5.45	5.53	5.11	25.27	-30.7	-16.9	-47.0	6.83	4.14	-66.9	-90.9	-114.7	-135.1	8.5	-89.52
1.25	100.94	846.3	822.1	813.2	5.53	5.53	4.98	25.26	-29.9	-16.5	-47.7	6.54	3.90	-65.8	-90.6	-115.0	-135.4	10.0	-91.88
1.50	103.14	871.3	847.4	839.3	5.44	5.51	4.86	25.23	-29.3	-17.0	-48.3	6.21	4.77	-66.2	-91.1	-115.5	-135.9	20.8	-101.12
1.75	103.69	896.6	873.2	865.5	5.30	5.41	4.70	25.20	-31.3	-17.8	-49.0	5.54	2.98	-65.7	-91.1	-116.5	-136.7	35.5	-107.19
2.00	102.65	921.9	899.1	891.8	5.23	5.23	4.45	25.17	-30.6	-18.2	-48.8	4.99	3.87	-66.3	-90.9	-117.0	-137.4	60.7	-112.67
2.25	102.50	947.2	924.7	917.9	5.19	5.15	4.25	25.14	-30.8	-19.5	-49.4	4.73	4.49	-66.5	-92.0	-117.1	-138.0	86.7	-116.30
2.50	102.59	972.6	950.4	943.9	5.10	5.07	4.06	25.11	-30.9	-19.6	-50.8	4.73	2.06	-65.7	-91.6	-117.6	-138.3	100.0	-117.70
2.75	100.57	997.8	976.0	970.1	5.01	4.98	3.80	25.09	-30.2	-20.5	-52.2	4.90	4.46	-66.9	-91.8	-117.4	-138.0	211.6	-124.34
3.00	97.50	1022.4	1001.2	995.9	4.98	4.86	3.62	25.09	-29.5	-20.9	-53.7	5.19	3.06	-66.1	-92.0	-117.3	-138.1	432.2	-130.85
3.25	95.33	1046.5	1025.5	1020.8	4.94	4.82	3.58	25.09	-29.5	-21.9	-55.4	5.68	3.15	-66.2	-91.5	-116.8	-137.7	507.5	-132.31
3.50	92.12	1069.9	1049.4	1045.3	4.86	4.78	3.52	25.09	-28.6	-22.9	-58.0	6.22	4.60	-65.3	-92.3	-116.7	-137.6	712.4	-135.31
3.75	87.50	1092.4	1072.4	1068.8	4.78	4.71	3.53	25.10	-28.0	-23.8	-61.9	6.75	3.01	-66.0	-92.3	-116.5	-137.5	851.6	-136.78
4.00	83.23	1113.6	1094.3	1090.9	4.68	4.64	3.57	25.11	-26.1	-26.7	-64.5	7.19	2.95	-67.6	-91.6	-116.4	-137.2	1000.0	-138.40

*at 25°C unless mentioned otherwise

