

Power Splitter/Combiner

2 Way-90° 50Ω 330 to 580 MHz

QCN-5D+



CASE STYLE: FV1206-1

PRICE: \$4.45 ea. QTY (20)

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Available Tape and Reel at no extra cost
Reel Size Devices/Reel
7" 20, 50, 100, 200, 500, 1000, 3000

Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
Power Input (as a splitter)	15W* max.

* Derate linearly to 7W at 100°C ambient.
Permanent damage may occur if any of these limits are exceeded.

Pin Connections

SUM PORT	1
PORT 1 (0°)	4
PORT 2 (+90°)	6
GROUND	2,5
50 OHM TERM EXTERNAL	3

Features

- low insertion loss, 0.4 dB typ.
- high isolation, 22 dB typ.
- wrap-around terminal for excellent solderability
- ultra small, 0.12"X0.06"X0.035"
- patent pending

Applications

- balanced amplifiers
- modulators
- VHF
- defense communication

Electrical Specifications




FREQ. RANGE (MHz)	ISOLATION (dB)	INSERTION LOSS (dB) Avg. of Coupled Outputs ABOVE 3 dB	PHASE UNBALANCE (Degrees)	AMPLITUDE UNBALANCE (dB)	VSWR (:1)
$f_L - f_U$	Typ. Min.	Typ. Max.	Typ. Max.	Typ. Max.	Typ.
330-580					
330-400	20 17	0.3 0.6	2.5 5	0.6 1.1	1.2
400-525	20 16	0.4 0.7	2.5 4	0.2 0.5	1.2
525-580	18 14	0.6 0.9	1 4	0.8 1.6	1.2

1. For applications requiring DC voltage to be applied to the RF ports. DC resistance to ground is 100 Mohms min.


Typical Performance Data

Frequency (MHz)	Total Loss ¹ (dB)	Amplitude Unbalance (dB)	Isolation (dB)	Phase Unbalance (deg.)	VSWR S	VSWR 1	VSWR 2
	S-1 S-2						
330.00	2.95 3.75	0.81	22.84	87.70	1.15	1.20	1.13
340.00	3.02 3.67	0.66	22.76	87.70	1.15	1.20	1.14
360.00	3.15 3.54	0.39	22.58	87.71	1.15	1.20	1.14
380.00	3.27 3.44	0.17	22.39	87.72	1.15	1.21	1.15
400.00	3.37 3.36	0.01	22.16	87.76	1.15	1.22	1.16
410.00	3.41 3.33	0.08	22.02	87.81	1.15	1.22	1.17
430.00	3.48 3.30	0.18	21.70	87.89	1.16	1.23	1.19
470.00	3.55 3.31	0.24	20.79	88.22	1.17	1.26	1.23
480.00	3.56 3.33	0.22	20.51	88.34	1.18	1.27	1.24
500.00	3.55 3.40	0.15	19.91	88.64	1.20	1.30	1.28
510.00	3.54 3.45	0.08	19.57	88.84	1.21	1.31	1.30
530.00	3.49 3.58	0.09	18.83	89.34	1.23	1.34	1.34
550.00	3.43 3.76	0.33	17.98	90.03	1.26	1.39	1.39
570.00	3.36 4.01	0.66	17.04	91.03	1.31	1.44	1.46
580.00	3.31 4.17	0.85	16.55	91.66	1.33	1.48	1.50

1. Total Loss = Insertion Loss + 3dB splitter loss.




electrical schematic (Note 1)




For detailed performance specs & shopping online see web site

Outline Drawing



PCB Land Pattern




Suggested Layout,
Tolerance to be within ±.002

Outline Dimensions (inch/mm)

A	B	C	D	E	F
.126	.063	.035	.024	.022	.011
3.20	1.60	0.89	0.61	0.56	0.28
G	H	J	K		wt
.039	.024	.042	.123		grams
0.99	0.61	1.07	3.12		.020

Demo Board MCL P/N: TB-255+ Suggested PCB Layout (PL-131)



- NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS R04350B WITH DIELECTRIC THICKNESS 0.020" ± 0.0015"; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
3. DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
4. DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com
IFIRF MICROWAVE COMPONENTS

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

REV. M
M132682
QCN-5D+
AD/RS/CP/AM
130226