

Power Splitter/Combiner

2 Way-90° 50Ω 450 to 750 MHz

QCN-8+



CASE STYLE: FV1206-1

PRICE: \$4.45 ea. QTY (20)

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Available Tape and Reel at no extra cost

Reel Size	Devices/Reel
7"	20, 50, 100, 200, 500, 1000, 3000

Maximum Ratings

Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
Power Input (as a splitter)	15W* max.

* Derate linearly to 7W at 100°C ambient.
Permanent damage may occur if any of these limits are exceeded.

Pin Connections

SUM PORT	1
PORT 1 (0°)	4
PORT 2 (+90°)	6
GROUND	2,5
50 OHM TERM EXTERNAL	3

Features

- low insertion loss, 0.6 dB typ.
- wrap-around terminal for excellent solderability
- ultra small, 0.12"X0.06"X0.035"

Applications

- UHF
- balanced amplifiers
- modulators
- point to point radio

Electrical Specifications


FREQ. RANGE (MHz)	ISOLATION (dB)		INSERTION LOSS (dB) Avg. of Coupled Outputs ABOVE 3 dB		PHASE UNBALANCE (Degrees)		AMPLITUDE UNBALANCE (dB)		VSWR (:1)
$f_L - f_U$	Typ.	Min.	Typ.	Max.	Typ.	Max.	Typ.	Max.	Typ.
450-750	16	13	0.6	0.9	5	8	0.5	1.0	1.4
470-700	16	13	0.5	0.8	5	8	0.3	0.8	1.4

Typical Performance Data

Frequency (MHz)	Total Loss ¹ (dB)		Amplitude Unbalance (dB)	Isolation (dB)	Phase Unbalance (deg.)	VSWR S	VSWR 1	VSWR 2
	S-1	S-2						
450.00	3.27	3.76	0.49	15.68	85.22	1.41	1.41	1.38
460.00	3.32	3.71	0.40	15.70	85.29	1.40	1.41	1.38
470.00	3.36	3.67	0.31	15.72	85.37	1.40	1.41	1.37
510.00	3.49	3.53	0.04	15.84	85.66	1.39	1.40	1.36
550.00	3.58	3.45	0.13	15.95	86.00	1.37	1.40	1.36
570.00	3.61	3.43	0.18	16.01	86.18	1.37	1.40	1.36
590.00	3.63	3.42	0.20	16.07	86.37	1.36	1.40	1.36
610.00	3.63	3.43	0.20	16.12	86.62	1.36	1.40	1.36
630.00	3.62	3.46	0.17	16.16	86.85	1.36	1.40	1.37
650.00	3.60	3.50	0.11	16.18	87.12	1.36	1.41	1.38
670.00	3.57	3.56	0.01	16.19	87.43	1.37	1.41	1.39
690.00	3.53	3.64	0.11	16.19	87.77	1.37	1.43	1.40
710.00	3.48	3.74	0.27	16.17	88.15	1.38	1.44	1.42
730.00	3.41	3.87	0.46	16.13	88.60	1.40	1.46	1.45
750.00	3.33	4.03	0.70	16.07	89.12	1.41	1.48	1.48

1. Total Loss = Insertion Loss + 3dB splitter loss.


Outline Drawing






Outline Dimensions (inch/mm)

A	B	C	D	E	F
.126	.063	.035	.024	.022	.011
3.20	1.60	0.89	0.61	0.56	0.28
G	H	J	K		wt
.039	.024	.042	.123		grams
0.99	0.61	1.07	3.12		.020


Demo Board MCL P/N: TB-255+ Suggested PCB Layout (PL-131)



- NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS 0.020" ± 0.0015"; COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
3. DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
4. DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK



electrical schematic



For detailed performance specs & shopping online see web site

Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED
The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

REV. B
M127604
QCN-8+
ED-11876D/1
AD/CP/AM
130226