

Surface Mount

Power Splitter/Combiner

SCQA-4-162+

4 Way Quadrifilar 50Ω 1200 to 1600 MHz


Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-55°C to 100°C
Power Input (as a splitter)	1W max.
Internal Dissipation	0.20W max.
Permanent damage may occur if any of these limits are exceeded.	

Pin Connections

SUM PORT	10
PORT 1 (0°)	1
PORT 2 (90°)	2
PORT 3 (180°)	3
PORT 4 (270°)	4
GROUND	5,6,7,8,9,11,12


Outline Drawing



Outline Dimensions (inch/mm)

A	B	C	D	E	F	G	H	J	K	L	M	N	P	Q	T	wt. grams
.500	.500	.180	.100	.080	.115	.060	.040	.540	.060	.100	.135	.135	.140	.080		1.0
12.70	12.70	4.57	2.54	2.03	2.92	1.52	1.02	13.72	1.52	2.54	3.43	3.43	2.92	3.56	2.03	

Demo Board MCL P/N: TB-652+ Suggested PCB Layout (PL-368+)



- NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS' R04350B WITH DIELECTRIC THICKNESS .030" ± .002". COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.
3. DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
4. DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

Features

- good isolation, 22 dB typ.
- good phase unbalance, 3 deg.
- good matching VSWR, 1.15:1 typ.

Applications

- GPS phase array antenna



CASE STYLE: CK1704
PRICE: \$24.95 ea. QTY. (1-9)

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Electrical Specifications at 25°C

Parameter	Frequency (MHz)	Min.	Typ.	Max.	Unit
Frequency Range		1200	—	1600	MHz
Insertion Loss Above 6.0 dB	1200-1600	—	1.5	2.8	dB
Isolation	1200-1600	18	22	—	dB
Phase Unbalance	1200-1600	—	3.0	10	Degree
Amplitude Unbalance	1200-1600	—	0.6	1.0	dB
VSWR (Port S)	1200-1600	—	1.2	—	:1
VSWR (Port 1-4)	1200-1600	—	1.4	—	:1


*Phase Unbalance is referenced insertion phase at 0° port.

Typical Performance Data

Freq. (MHz)	Total Loss ¹ (dB)	Amp. Unbal. (dB)	Insertion Phase (deg)	Phase Unbalance (deg.)				Isolation (dB)			VSWR S	VSWR 1	VSWR 2	VSWR 3	VSWR 4
	S-1		S-1	0°	90°	180°	270°	1-2	2-3	3-4					
1150.00	6.98	0.32	160.79	0.00	88.03	179.66	267.65	22.35	31.34	25.42	1.09	1.03	1.04	1.07	1.02
1200.00	7.10	0.18	144.77	0.00	88.25	179.80	267.68	22.07	30.71	25.20	1.10	1.03	1.06	1.07	1.02
1225.00	7.16	0.26	136.76	0.00	88.37	179.89	267.72	21.94	30.39	25.11	1.11	1.03	1.06	1.07	1.03
1250.00	7.21	0.33	128.75	0.00	88.49	179.96	267.76	21.82	30.06	25.02	1.11	1.03	1.07	1.07	1.03
1275.00	7.26	0.38	120.75	0.00	88.62	180.02	267.82	21.72	29.69	24.95	1.11	1.03	1.07	1.08	1.04
1300.00	7.31	0.43	112.75	0.00	88.76	180.07	267.88	21.65	29.32	24.90	1.11	1.04	1.08	1.08	1.04
1350.00	7.38	0.51	96.73	0.00	89.04	180.18	268.04	21.54	28.55	24.88	1.11	1.04	1.09	1.09	1.05
1400.00	7.44	0.54	80.72	0.00	89.32	180.28	268.21	21.52	27.81	24.98	1.12	1.05	1.10	1.10	1.06
1450.00	7.48	0.54	64.73	0.00	89.60	180.32	268.38	21.59	27.08	25.19	1.12	1.06	1.10	1.11	1.07
1500.00	7.50	0.53	48.73	0.00	89.83	180.35	268.57	21.73	26.33	25.50	1.14	1.06	1.11	1.12	1.07
1525.00	7.50	0.51	40.73	0.00	89.96	180.35	268.67	21.83	26.00	25.70	1.15	1.07	1.11	1.13	1.08
1550.00	7.50	0.48	32.73	0.00	90.07	180.33	268.76	21.94	25.67	25.91	1.16	1.07	1.11	1.13	1.08
1575.00	7.49	0.44	24.73	0.00	90.18	180.30	268.87	22.07	25.33	26.16	1.18	1.07	1.11	1.14	1.08
1600.00	7.48	0.39	16.75	0.00	90.28	180.25	268.98	22.23	25.02	26.43	1.20	1.08	1.11	1.14	1.09
1650.00	7.46	0.30	0.72	0.00	90.48	180.20	269.22	22.57	24.40	26.99	1.23	1.08	1.11	1.14	1.10

1. Total Loss = Insertion Loss + 6dB splitter loss.

Phase Diagram



Electrical Configuration



Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED
The Design Engineers Search Engine Provides ACTUAL Data Instantly at minicircuits.com
IF/RF MICROWAVE COMPONENTS

For detailed performance specs & shopping online see web site

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuits' applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

REV. A
M140239
SCQA-4-162+
ED-14652/1
AB/CP/AM
130118

Performance Charts

SCQA-4-162+

