

Coaxial

Power Splitter/Combiner

16 Way-0° 50Ω 700 to 1000 MHz

ZC16PD-960W+

Maximum Ratings


Operating Temperature	-55°C to 100°C
Storage Temperature	-55°C to 100°C
Power Input (as a splitter)	10W max.
Internal Dissipation	2.4W max.

Permanent damage may occur if any of these limits are exceeded.

Coaxial Connections

SUM PORT	S
PORT 1,2,3,.....,16	1,2,3,.....,16

Outline Drawing



Outline Dimensions (inch/mm)


A	B	C	D	E	F	G
8.50	3.95	.75	.250	8.250	—	.187
215.90	100.33	19.05	6.35	209.55	—	4.75
H	J	K	L	M	wt	
4.250	.38	.500	.475	3.475	grams	
107.95	9.65	12.70	12.07	88.27	710	

Features

- low insertion loss, 0.5 dB typ.
- excellent VSWR, 1.1:1 typ.
- good isolation, 28 dB typ.

Applications

- UHF
- cellular
- communication systems



CASE STYLE: UU179

Connectors	Model	Price	Qty.
SMA	ZC16PD-960W-S+	\$265.00	(1-9)

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications




Electrical Specifications

FREQ. RANGE (MHz)	ISOLATION (dB)	INSERTION LOSS (dB) ABOVE 12 dB	PHASE UNBALANCE (Degrees)	AMPLITUDE UNBALANCE (dB)	VSWR (:1)
f_L - f_U	Typ. Min.	Typ. Max.	Max.	Max.	S OUT Typ. Max. Typ. Max.
700-1000	26 15	0.5 1.3	—	0.6	1.1 1.6 1.06 1.3

Typical Performance Data

Freq. (MHz)	Total Loss ¹ (dB)	Amplitude Unbalance (dB)	Isolation (dB)	Phase Unbalance (deg.)	VSWR S	VSWR 1
	S-1		1-2 3-4			
700.00	12.39	0.32	22.85 23.16	11.15	1.29	1.11
720.00	12.42	0.29	24.01 24.35	11.49	1.31	1.10
740.00	12.46	0.29	25.22 25.61	11.19	1.32	1.10
770.00	12.45	0.38	27.25 27.69	11.43	1.30	1.09
800.00	12.48	0.28	29.48 29.88	12.12	1.25	1.08
815.00	12.47	0.27	30.55 30.81	12.09	1.21	1.07
830.00	12.49	0.24	31.50 31.56	12.16	1.18	1.07
845.00	12.49	0.25	32.20 31.98	12.05	1.14	1.06
860.00	12.42	0.26	32.41 31.88	12.23	1.10	1.06
875.00	12.43	0.35	32.22 31.45	12.83	1.08	1.05
890.00	12.46	0.35	31.64 30.73	13.20	1.06	1.04
920.00	12.45	0.33	29.71 28.76	13.21	1.04	1.03
950.00	12.47	0.22	27.55 26.73	13.48	1.07	1.02
980.00	12.55	0.23	25.43 24.75	14.45	1.16	1.02
1000.00	12.60	0.21	24.12 23.52	14.54	1.26	1.02

1. Total Loss = Insertion Loss + 12dB splitter loss.



electrical schematic



Mini-Circuits®
ISO 9001 ISO 14001 AS 9100 CERTIFIED

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661 The Design Engineers Search Engine [minicircuits.com](http://www.minicircuits.com) Provides ACTUAL Data Instantly at [minicircuits.com](http://www.minicircuits.com)

Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

For detailed performance specs
& shopping online see web site

REV. B
M131858
ZC16PD-960W+
HY/TD/CP/AM
120427