

Frequency Synthesizer

KSN-2675A-119+

50Ω 2475 to 2675 MHz

The Big Deal

- Fractional N synthesizer
- Low phase noise and spurious
- Robust design and construction
- Small size 0.80" x 0.58" x 0.15"



CASE STYLE: DK1042

Product Overview

The KSN-2675A-119+ is a Frequency Synthesizer, designed to operate from 2475 to 2675 MHz for WiMAX application. The KSN-2675A-119+ is packaged in a metal case (size of 0.80" x 0.58" x 0.15") to shield against unwanted signals and noise.

Key Features

Feature	Advantages
Low phase noise and spurious: • Phase Noise:-101 dBc/Hz typ. @ 10 kHz offset • Step Size Spurious:-100 dBc typ. • Comparison Spurious: -100 dBc typ. • Reference Spurious: -100 dBc typ.	Low phase noise and spurious improve system EVM (Error Vector Magnitude).
Robust design and construction	To enhance the robustness of KSN-2675A-119+, each internal component is secured to the substrate with chip bonder, thereby eliminating the risk of tombstoning during subsequent solder reflow operations by the customer.
Small size, 0.80" x 0.58" x 0.15"	The small size enables the KSN-2675A-119+ to be used in compact designs.



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCStore/terms.jsp.

50Ω 2475 to 2675 MHz

Features

- Fractional N synthesizer
- Integrated VCO + PLL
- Low phase noise and spurious
- Robust design and construction
- Low operating voltage (VCC VCO=+5V, VCC PLL=+3V)
- Small size 0.80" x 0.58" x 0.15"

Applications

- WiMAX

General Description

The KSN-2675A-119+ is a Frequency Synthesizer, designed to operate from 2475 to 2675 MHz for WiMAX application. The KSN-2675A-119+ is packaged in a metal case (size of 0.80" x 0.58" x 0.15") to shield against unwanted signals and noise. To enhance the robustness of KSN-2675A-119+, each internal component is secured to the substrate with chip bonder, thereby eliminating the risk of tombstoning during subsequent solder reflow operations by the customer.




CASE STYLE: DK1042

PRICE: \$29.95 ea. QTY (1-9)

+ RoHS compliant in accordance with EU Directive (2002/95/EC)

The +Suffix has been added in order to identify RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications.

Simplified Schematic



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCStore/terms.jsp.

REV. OR
M126669
EDR-8854/1F1
KSN-2675A-119+
Category-A2
RAV
100323
Page 2 of 11

Electrical Specifications (over operating temperature -40°C to +85°C)

Parameters		Test Conditions	Min.	Typ.	Max.	Units
Frequency Range		-	2475	-	2675	MHz
Step Size		-	-	250	-	kHz
Comparison Frequency		-	-	10	-	MHz
Settling Time		Within ± 1 kHz	-	26	-	mSec
Output Power		-	-1	+2	+5	dBm
SSB Phase Noise	@ 100 Hz offset		-	-76	-	dBc/Hz
	@ 1 kHz offset		-	-85	-77	
	@ 10 kHz offset		-	-101	-96	
	@ 100 kHz offset		-	-125	-120	
	@ 1 MHz offset		-	-145	-140	
Step Size Spurious Suppression		Step Size 250 kHz	-	-100	-88	dBc
0.5 Step Size Spurious Suppression		0.5 Step Size 125 kHz	-	-88	-70	
Reference Spurious Suppression		Ref. Freq. 10MHz	-	-100	-80	
Comparison Spurious Suppression		Comp. Freq. 10MHz	-	-100	-80	
Non - Harmonic Spurious Suppression		-	-	-90	-	
Harmonic Suppression		-	-	-33	-26	V
VCO Supply Voltage		+5.00	+4.75	+5.00	+5.25	
PLL Supply Voltage		+3.00	+2.85	+3.00	+3.15	mA
VCO Supply Current		-	-	46	53	
PLL Supply Current		-	-	14	22	
Reference Input (External)	Frequency	10 (square wave)	-	10	-	MHz
	Amplitude	1	-	1	-	V _{P-P}
	Input impedance	-	-	100	-	K Ω
	Phase Noise @ 1 kHz offset	-	-	-145	-	dBc/Hz
RF Output port Impedance		-	-	50	-	Ω
Input Logic Level	Input high voltage	-	2.55	-	-	V
	Input low voltage	-	-	-	0.55	V
Digital Lock Detect	Locked	-	2.45	-	3.15	V
	Unlocked	-	-	-	0.40	V
Frequency Synthesizer PLL		-	ADF4153			
PLL Programming		-	3-wire serial 3V CMOS			
Register Map @ 2675 MHz	R0_Register	-	(MSB) 010000101100000001010000 (LSB)			
	R1_Register	-	(MSB) 0001010001000000010100001 (LSB)			
	R2_Register	-	(MSB) 0000000111000010 (LSB)			
	R3_Register	-	(MSB) 01111000111 (LSB)			

Absolute Maximum Ratings

Parameters	Ratings
VCO Supply Voltage	5.8V
PLL Supply Voltage	4.0V
VCO Supply Voltage to PLL Supply Voltage	-0.3V to +5.8V
Reference Frequency Voltage	-0.3Vmin, VCC PLL +0.3Vmax
Data, Clock, LE Levels	-0.3Vmin, VCC PLL +0.3Vmax
Operating Temperature	-40°C to +85°C
Storage Temperature	-55°C to +100°C

Permanent damage may occur if any of these limits are exceeded



Typical Performance Data

FREQUENCY (MHz)	POWER OUTPUT (dBm)			VCO CURRENT (mA)			PLL CURENT (mA)		
	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
2475	2.47	2.22	1.81	43.86	46.00	47.31	12.85	14.14	16.63
2495	2.44	2.19	1.80	43.95	46.13	47.42	12.83	14.05	16.69
2515	2.47	2.18	1.82	44.04	46.11	47.51	12.79	14.04	16.67
2535	2.55	2.26	1.87	44.13	46.24	47.59	12.71	14.10	16.60
2555	2.62	2.37	1.96	44.25	46.41	47.69	12.74	13.82	16.64
2575	2.63	2.41	2.02	44.35	46.52	47.79	12.85	13.45	16.78
2595	2.59	2.37	1.99	44.42	46.59	47.86	12.75	14.14	16.68
2615	2.54	2.28	1.91	44.50	46.67	47.93	12.71	14.06	16.65
2635	2.56	2.29	1.89	44.58	46.75	48.02	12.78	14.04	16.74
2655	2.61	2.33	1.92	44.65	46.82	48.09	12.83	14.11	16.80
2675	2.63	2.36	2.01	44.71	46.88	48.14	12.85	14.17	16.82

FREQUENCY (MHz)	HARMONICS (dBc)					
	F2			F3		
	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
2475	-36.00	-32.81	-30.30	-54.83	-47.77	-56.41
2495	-35.35	-33.46	-30.33	-51.11	-45.56	-50.66
2515	-35.00	-33.62	-30.83	-48.73	-41.82	-47.57
2535	-35.65	-33.55	-31.42	-48.73	-40.40	-45.64
2555	-34.42	-33.24	-30.93	-50.68	-41.51	-44.81
2575	-34.88	-33.01	-30.61	-57.68	-43.85	-44.90
2595	-33.73	-33.61	-31.09	-52.30	-45.68	-45.00
2615	-33.14	-33.67	-31.43	-50.95	-47.09	-45.49
2635	-33.44	-33.51	-31.74	-51.35	-48.05	-45.45
2655	-33.16	-32.76	-31.27	-49.83	-49.77	-45.59
2675	-32.93	-32.72	-30.87	-46.28	-52.85	-45.79



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCStore/terms.jsp.

FREQUENCY (MHz)	PHASE NOISE (dBc/Hz) @ OFFSETS				
	+25°C				
	100Hz	1kHz	10kHz	100kHz	1MHz
2475	-86.55	-87.90	-101.65	-125.76	-145.82
2495	-85.43	-86.00	-101.92	-126.02	-146.31
2515	-85.08	-86.05	-101.50	-125.68	-146.00
2535	-85.15	-85.97	-101.10	-125.35	-145.82
2555	-85.24	-85.76	-100.90	-125.30	-145.79
2575	-84.98	-85.65	-100.81	-125.42	-145.77
2595	-84.20	-85.32	-100.61	-125.22	-145.68
2615	-84.14	-84.36	-100.48	-125.09	-145.62
2635	-84.93	-84.17	-100.58	-125.02	-145.50
2655	-85.51	-83.57	-100.72	-124.96	-145.39
2675	-83.98	-84.42	-100.54	-124.78	-145.18

FREQUENCY (MHz)	PHASE NOISE (dBc/Hz) @ OFFSETS				
	-45°C				
	100Hz	1kHz	10kHz	100kHz	1MHz
2475	-82.58	-86.67	-102.37	-126.95	-147.39
2495	-83.40	-85.99	-102.08	-126.85	-147.37
2515	-84.03	-85.42	-101.52	-126.54	-147.15
2535	-82.74	-85.31	-101.32	-126.40	-146.97
2555	-80.70	-85.62	-101.39	-126.45	-147.14
2575	-81.34	-84.99	-101.08	-126.31	-147.11
2595	-81.44	-85.21	-100.73	-126.24	-146.84
2615	-82.67	-85.15	-100.78	-126.24	-146.71
2635	-82.24	-84.57	-100.58	-126.12	-146.73
2655	-81.53	-83.77	-100.60	-125.93	-146.67
2675	-80.69	-83.34	-100.85	-125.76	-146.41

FREQUENCY (MHz)	PHASE NOISE (dBc/Hz) @ OFFSETS				
	+85°C				
	100Hz	1kHz	10kHz	100kHz	1MHz
2475	-84.09	-85.67	-101.05	-124.30	-144.28
2495	-84.33	-84.94	-101.32	-124.15	-144.67
2515	-85.04	-83.95	-100.51	-123.93	-144.45
2535	-83.85	-84.04	-99.91	-123.95	-144.31
2555	-86.12	-85.42	-99.65	-124.05	-144.41
2575	-83.59	-84.65	-99.90	-124.17	-144.55
2595	-85.75	-85.02	-99.94	-123.90	-144.31
2615	-83.51	-83.86	-99.80	-123.85	-144.34
2635	-82.05	-82.57	-99.89	-123.75	-144.35
2655	-81.12	-82.63	-100.09	-123.60	-144.25
2675	-84.27	-81.83	-100.17	-123.76	-143.71



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCStore/terms.jsp.

REFERENCE & COMPARISON SPURIOUS ORDER	REFERENCE & COMPARISON SPURIOUS @Fcarrier 2475MHz+(n*Fcomp or Fref) (dBc) note 1			REFERENCE & COMPARISON SPURIOUS @Fcarrier 2575MHz+(n*Fcomp or Fref) (dBc) note 1			REFERENCE & COMPARISON SPURIOUS @Fcarrier 2675MHz+(n*Fcomp or Fref) (dBc) note 1		
	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
-5	-104.17	-101.57	-104.67	-101.89	-105.63	-105.13	-106.20	-103.56	-109.67
-4	-106.74	-99.78	-103.28	-100.98	-102.50	-102.75	-104.72	-101.07	-105.89
-3	-104.50	-97.33	-100.79	-98.07	-101.11	-101.30	-101.21	-101.28	-106.27
-2	-103.34	-95.87	-98.02	-96.47	-98.17	-98.70	-98.10	-98.75	-99.70
-1	-99.02	-98.52	-107.97	-98.59	-101.64	-98.88	-101.37	-110.34	-91.47
0 note 4	-	-	-	-	-	-	-	-	-
+1	-101.83	-95.56	-94.64	-97.54	-101.29	-96.71	-98.99	-106.66	-94.53
+2	-101.75	-98.65	-100.20	-98.14	-100.52	-99.63	-98.81	-97.75	-102.33
+3	-104.57	-100.32	-103.33	-101.27	-103.36	-101.22	-100.90	-99.23	-106.94
+4	-104.87	-101.87	-100.62	-101.39	-102.88	-100.50	-101.67	-99.43	-104.37
+5	-106.75	-104.71	-104.09	-105.16	-106.33	-102.55	-103.05	-102.46	-109.81

Note 1: Comparison frequency = reference frequency = 10 MHz

Note 2: All spurs are referenced to carrier signal (n=0).

STEP SIZE SPURIOUS ORDER	0.5 STEP SIZE & STEP SIZE SPURIOUS @Fcarrier 2475MHz+(n*Fstep size) (dBc) note 5			0.5 STEP SIZE & STEP SIZE SPURIOUS @Fcarrier 2575MHz+(n*Fstep size) (dBc) note 5			0.5 STEP SIZE & STEP SIZE SPURIOUS @Fcarrier 2675MHz+(n*Fstep size) (dBc) note 5		
	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C	-45°C	+25°C	+85°C
-5.0	-115.51	-110.63	-111.05	-110.20	-120.46	-120.08	-117.33	-112.22	-111.43
-4.5	-114.72	-109.50	-107.11	-117.01	-121.29	-120.40	-119.72	-111.11	-119.38
-4.0	-120.59	-113.57	-112.63	-119.57	-119.04	-118.85	-116.39	-119.94	-118.35
-3.5	-114.40	-116.44	-116.09	-107.16	-117.80	-118.01	-106.81	-115.55	-112.09
-3.0	-118.06	-119.23	-109.31	-111.08	-118.58	-114.37	-109.96	-115.66	-113.29
-2.5	-109.34	-103.43	-102.91	-109.95	-116.15	-114.55	-114.05	-110.39	-105.87
-2.0	-104.68	-115.56	-108.94	-105.79	-113.49	-109.23	-106.08	-114.64	-109.75
-1.5	-106.13	-100.54	-101.35	-105.27	-106.45	-104.67	-105.14	-107.78	-100.18
-1.0	-104.24	-99.49	-99.75	-101.86	-99.49	-102.64	-101.93	-99.18	-101.18
-0.5	-89.68	-88.45	-91.29	-84.45	-87.12	-85.69	-80.05	-87.86	-86.18
0 note 6	-	-	-	-	-	-	-	-	-
+0.5	-89.55	-89.58	-88.78	-83.44	-87.70	-85.36	-81.54	-88.61	-87.61
+1.0	-103.45	-99.03	-100.12	-103.25	-104.07	-98.53	-99.43	-104.64	-101.76
+1.5	-102.16	-101.51	-107.67	-106.52	-110.25	-105.04	-101.94	-104.21	-102.23
+2.0	-102.63	-112.61	-107.00	-105.19	-113.69	-113.30	-104.78	-112.62	-109.06
+2.5	-109.59	-104.62	-103.42	-107.88	-114.70	-114.77	-113.72	-107.20	-105.25
+3.0	-116.45	-114.31	-112.07	-111.28	-116.33	-119.30	-113.05	-117.74	-112.90
+3.5	-113.42	-117.68	-117.08	-108.53	-119.41	-117.48	-108.96	-115.83	-111.67
+4.0	-122.31	-110.85	-114.16	-120.38	-114.96	-119.74	-116.24	-117.46	-118.09
+4.5	-112.60	-113.91	-113.17	-114.35	-114.73	-119.68	-119.49	-115.33	-115.55
+5.0	-112.43	-110.81	-117.61	-110.46	-114.76	-118.93	-120.81	-107.67	-119.82

Note 3: Step size frequency 250 kHz

Note 4: All spurs are referenced to carrier signal (n=0).



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS 9100 CERTIFIED RoHS compliant

P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661




The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see




Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCStore/terms.jsp.

Typical Performance Curves


OUTPUT POWER Vs FREQUENCY



2nd HARMONIC Vs FREQUENCY



3rd HARMONIC Vs FREQUENCY








IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCStore/terms.jsp.









IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

REFERENCE & COMPARISON SPURIOUS
Vs FREQ. OFFSET @ Fcar = 2475MHz0.5 STEP SIZE & STEP SIZE SPURIOUS
Vs FREQ. OFFSET @ Fcar = 2475MHzREFERENCE & COMPARISON SPURIOUS
Vs FREQ. OFFSET @ Fcar = 2575MHz0.5 STEP SIZE & STEP SIZE SPURIOUS
Vs FREQ. OFFSET @ Fcar = 2575MHzREFERENCE & COMPARISON SPURIOUS
Vs FREQ. OFFSET @ Fcar = 2675MHz0.5 STEP SIZE & STEP SIZE SPURIOUS
Vs FREQ. OFFSET @ Fcar = 2675MHz

IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661




The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.

Pin Configuration




Pin Connection


Pin Number	Function
1	VCC PLL
2	GND
3	REF IN
4	GND
5	VCC VCO
6	GND
7	RF OUT
8	GND
9	LOCK DET
10	CLOCK
11	DATA
12	LE
13	GND
14	GND

Recommended Application Circuit

Note: REF IN and RF OUT ports are internally AC coupled.



Device Marking

**Additional Detailed Technical Information**

Additional information is available on our web site. To access this information enter the model number on our web site home page.

Case Style: DK1042

Tape & Reel: TR-F28

Suggested Layout for PCB Design: PL-249

Evaluation Board: TB-567-2+

Environment Ratings: ENV03T2



IF/RF MICROWAVE COMPONENTS • ISO 9001 ISO 14001 AS9100 CERTIFIED RoHS compliant
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661



The Design Engineers Search Engine finds the model you need, Instantly • For detailed performance specs & shopping online see



Notes: 1. Performance and quality attributes and conditions not expressly stated in this specification sheet are intended to be excluded and do not form a part of this specification sheet. 2. Electrical specifications and performance data contained herein are based on Mini-Circuit's applicable established test performance criteria and measurement instructions. 3. The parts covered by this specification sheet are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp.