



- **OUTPUT VOLTAGE RANGE ADJUSTABLE:**
1.25 TO 40V FOR STANDARD VERSION
1.25 TO 60V FOR –HV VERSION
- **1% OUTPUT VOLTAGE TOLERANCE**
(–A VERSIONS)
- **0.3% LOAD REGULATION**
- **0.01%/V LINE REGULATION**
- **COMPLETE SERIES OF PROTECTIONS:**
 - **CURRENT LIMITING**
 - **THERMAL SHUTDOWN**
 - **SOA CONTROL**

DESCRIPTION

Over full operating conditions, including load, line, and power dissipation, the reference voltage is guaranteed not to vary more than 2%. These devices exhibit current limit, thermal overload protection, and improved power device safe operating area protection, making them essentially indestructible.

ABSOLUTE MAXIMUM RATINGS (T_{case} = 25°C unless otherwise stated)

V _{I-O}	Input - Output Differential Voltage	– Standard	40V
		– HV Series	60V
P _D	Power Dissipation		Internally limited
T _J	Operating Junction Temperature Range		–55 to 150°C
T _{STG}	Storage Temperature		–65 to 150°C

Document Number 5383
Issue 1

Parameter	Test Conditions	IP117MAHV IP117MA			IP117MHV , IP117M			Units
		Min.	Typ.	Max.	Min.	Typ.	Max.	
V_{REF} Reference Voltage	$I_{OUT} = 10mA$	1.238	1.25	1.262				V
	$I_{OUT} = 10mA$ to I_{MAX} $V_{IN} - V_{OUT} = 3V$ to V_{MAX} $P \leq P_{MAX}$ $T_J = -55$ to $+150^\circ C$	1.220	1.250	1.270	1.200	1.250	1.300	V
$\frac{\Delta V_{OUT}}{\Delta V_{IN}}$ Line Regulation 1	$V_{IN} - V_{OUT} = 3V$ to V_{MAX} $T_J = -55$ to $+150^\circ C$		0.005	0.010		0.010	0.020	% / V
			0.010	0.020		0.020	0.050	
$\frac{\Delta V_{OUT}}{\Delta I_{OUT}}$ Load Regulation 1	$I_{OUT} = 10mA$ to I_{MAX} $T_J = -55$ to $+150^\circ C$	$V_{OUT} \leq 5V$		5	15	5	15	mV
		$V_{OUT} \geq 5V$		0.1	0.3	0.1	0.3	%
	$I_{OUT} = 10mA$ to I_{MAX} $T_J = -55$ to $+150^\circ C$	$V_{OUT} \leq 5V$		15	50	20	50	mV
		$V_{OUT} \geq 5V$		0.3	1	0.3	1	%
Thermal Regulation	$t_p = 20ms$		0.002	0.020		0.030	0.070	%/W
Ripple Rejection	$V_{OUT} = 10V$ $f = 120Hz$	$C_{ADJ} = 0$		65		65		dB
		$C_{ADJ} = 10\mu F$ $T_J = -55$ to $+150^\circ C$		66	80	66	80	dB
I_{ADJ} Adjust Pin Current	$T_J = -55$ to $+150^\circ C$		50	100		50	100	μA
ΔI_{ADJ} Adjust Pin Current Change	$I_{OUT} = 10mA$ to I_{MAX} $T_J = -55$ to $+150^\circ C$ $V_{IN} - V_{OUT} = 2.5V$ to V_{MAX}		0.2	5		0.2	5	μA
I_{MIN} Minimum Load Current	$V_{IN} - V_{OUT} = 40V$ $T_J = -55$ to $+150^\circ C$		3.5	5		3.5	5	mA
	$V_{IN} - V_{OUT} = 60V$ (HV SERIES) $T_J = -55$ to $+150^\circ C$		3.5	7		3.5	7	
I_{CL} Current Limit	$V_{IN} - V_{OUT} \leq 15V$ $T_J = -55$ to $+150^\circ C$	0.50	0.80		0.50	0.80		A
	$V_{IN} - V_{OUT} = 40V$	0.15	0.20		0.15	0.20		A
	$V_{IN} - V_{OUT} = 60V$ (HV SERIES)		0.30			0.30		
$\frac{\Delta V_{OUT}}{\Delta TEMP}$ Temperature Stability	$T_J = -55$ to $+150^\circ C$		1	2		1		%
$\frac{\Delta V_{OUT}}{\Delta TIME}$ Long Term Stability	$T_A = +125^\circ C$ $t = 1000$ Hrs		0.3	1		0.3	1	%
e_n RMS Output Noise (% of V_{OUT})	$f = 10$ Hz to 10 kHz		0.001			0.001		%
$R_{\theta JC}$ Thermal Resistance Junction to Case	LCC4 Package			13			13	$^\circ C/W$

1) Regulation is measured at constant junction temperature, using pulse testing at a low duty cycle. Changes in output voltage due to heating effects are covered under thermal regulation specifications.

2) Test Conditions unless otherwise stated: $V_{IN} - V_{OUT} = 5V$, $T_J = 25^\circ C$, $I_{OUT} = 0.1A$, $P_{MAX} = 10W$, $I_{MAX} = 0.5A$
 $V_{MAX} = 40V$ for standard series, $60V$ for HV series.

Semelab Plc reserves the right to change test conditions, parameter limits and package dimensions without notice. Information furnished by Semelab is believed to be both accurate and reliable at the time of going to press. However Semelab assumes no responsibility for any errors or omissions discovered in its use. Semelab encourages customers to verify that datasheets are current before placing orders.