


Model 6470 SMD Microtip Test Probe Set



FEATURES

- Replaceable tip probe set with spring-loaded pogo-pin triple-point SMD Microtip included. (Other tips are available, see model 6475)
- Fits most DMM's including Fluke, Wavetek Meterman, Greenlee, Amprobe, and others
- Thermoplastic elastomer outer coat provides comfortable grip and flexible strain relief
- Probe and banana plug are molded directly onto the wire for robust pull strength
- · Wire is a high strand count silicone wire for extreme flexibility and high temperature resistance
- Wear indication with double insulated (dual extruded) silicone leads shows white inner layer for increased safety
- Banana plug spring is Nickel-plated Beryllium Copper for long insertion life

MATERIALS

Probe:

Outer Insulation: Santoprene® rubber, gray Inner Insulation: polypropylene, black and red

Tip: Gold-plated Beryllium Copper Wire: 18 AWG Silicone insulated Banana Plug: Nickel-plated brass

Spring: Nickel-plated Beryllium Copper

Plug Insulation: Polypropylene, color: one black, one red

RATINGS

IEC 61010-031

Operating Voltage: CAT II 1000 V

Current: 5 Amperes

ORDERING INFORMATION

Model 6470

Includes a set of one black and one red test lead with two replaceable tips

USA: Sales: 800-490-2361

Technical Support: technicalsupport@pomonatest.com

Fax: 425-446-5844

Europe: 31-(0) 40 2675 150 International: 425-446-5500

Where to Buy: www.pomonaelectronics.com

All dimensions are in inches. Tolerances (except noted): $.xx = \pm .02$ " (,51 mm), $.xxx = \pm .005$ " (,127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.