




SERIES KL18

- 7 Pin Tubular High Security Key
- Max 1000 Key Codes



CHARACTERISTICS

- 7 Pin Tubular High Security Key
- 3 to 5 Indexing Positions
- 45°, 90°, Mixed 45° and 90° Detent Angles
- Single pole or Double pole Switching
- Max 1000 Key Codes

SPECIFICATIONS

Contact Rating: 4A @ 125 VAC or 28 VDC - 2A @ 250 VAC
Contact Resistance: <10 m Ω
Insulation Resistance: 1000 Ω min.
Dielectric Strength: 1000 V RMS Min @ sea level
Electric Life: 6.000 make & break cycles @ full load

MATERIALS

Lock Housing: Zinc alloy Die-casted & Nickel plated
Cylinder: 5 Disk tumbler in Zinc alloy Die-casted & Nickel plated
Keys: Brass or Brass Nickel-plated
Contacts: Hard Copper alloy Silver plated
Mounting Nut: Zinc alloy Die-casted & Nickel plated

HOW TO ORDER

K L 1 8 - 1 9

SERIES

CUT-OUT DIAMETER

P/N CONFIGURATOR

Choose:
 Nr of Positions
 Indexing
 Nr of Poles
 Layout
 Terminal Connections
 Key pull-out

OPTIONS

- (※) Same Key supplied standard
- (※) When ordering specify same Key or different Keys
(max as specified in characteristics)
- (※) Each Key is identified with a Key Code
- (※) Min Qty per lot apply for different Keys - Please enquire -
- (◊) Repeat orders can be supplied with specific Key Code
(subject to min lot orders) - Please enquire -
- (◊) Key Codes to fit other suppliers lock available on request - Please enquire -

