



**TECHNICAL DATA SHEET**  
**LITHIUM ION**  
**RECHARGEABLE BATTERY**

**PB-FE-01**



**BATTERY SPECIFICATIONS**

<b>Model No:</b> PB-FE-01	
<b>Manufacturers CAGE Code:</b> 03UN7	
<b>Voltage Range:</b> 3.0V min.; 3.7V nom.; 4.2V max.	
<b>Nominal Capacity:</b> 7.2 Ah @ 500mA @ 23°C (74°F)	
<b>Maximum Discharge:</b> 3.5 A continuous @ 23°C (74°F)	
<b>Maximum Pulse Discharge:</b> 6.0A for 5 seconds @ 23°C (74°F)	
<b>Energy:</b> 26 Wh	
<b>Energy Density:</b> 155 Wh/kg, 317 Wh/l	
<b>Weight:</b> 167 grams (0.367 lbs.) max.	
<b>Cycle Life:</b> > 300 cycles @ C/5 to 80% of initial capacity @ 100% depth of discharge	
<b>Operating Temp:</b> -20°C to 60°C (-4°F to 140°F)	
<b>Storage Temp:</b> -20°C to 60°C (-4°F to 140°F)	
<b>Self-Discharge:</b> < 3% per month	
<b>Housing:</b> Shrink Wrap	
<b>Connector:</b> Molex 502351-0400	
<b>Safety:</b> See Material Safety Datasheet – MSDS047	
<b>Transportation:</b> See MSDS047	
<b>Harmonized Tariff Code:</b> 8507.80.0000	
<b>Charging:</b> Charge at constant voltage of 4.2 Volts maximum in a temperature range of 0°C to 45°C, limiting current to 2.0 A max, at 23°C, until current declines to 100mA	

**APPLICATIONS**

- Back-up Server Power
- Ruggedized Portable Electronics

**KEY FEATURES**

- High energy density
- Long cycle life
- Lightweight

**COMPATIBLE CHARGERS**

- PC-6010/DP



**TECHNICAL DATA SHEET**  
**LITHIUM ION**  
**RECHARGEABLE BATTERY**

