



TECHNICAL DATA SHEET
LITHIUM ION
BATTERY CHARGER

PC-6150M



CHARGER SPECIFICATIONS

Model No: PC-6150M	NSN: TBD
Manufacturers CAGE Code: 03UN7	
AC Input Range: 95 to 265VAC; 47 to 63Hz	
Battery Charge Voltage: 4.2VDC max. per position	
Battery Charge Current: 4A max. per position	
Battery Connection: Contacts	
Led Indicators: Flashing green LED – Charging Solid green LED – Fully Charged Flashing red LED – Error Solid red LED – Waiting for Charging to Start	
Weight: 28 lbs. (13 Kg)	
Dimensions: 20" x 16 3/4" x 10 1/4" H (51cm x 43cm x 26cm)	
Operating / Charging Temp: 0° C to 50° C (32°F to 122°F)	
Storage Temp: -25° C to 70° C (-13°F to 158°F)	
Humidity: 95% relative	
Color: Black	
Exterior Carrying Case: Hard plastic case	
Harmonized Tariff Code: 8507.90.80.00	

APPLICATIONS

- Charging for remote, field and depot settings

KEY FEATURES

- Tactical, ruggedized, portable
- LED display for each battery charging position
- 15-position battery charging capability
- Unattended charging
- Ruggedized environment resistant case

BENEFITS

- Charges up to 15 batteries simultaneously
- Easy battery connection – no cables required
- Batteries contained in charger for charge cycle duration

CHARGES THE FOLLOWING BATTERIES

- PB-1301
- PB-1601
- PBH-1301
- PBH-1601