



**Features**

- Low power consumption
- Robust package
- I.C. Compatible
- Standard configuration: Gray face w/ white dots
- Optional black face provides superior color contrast
- RoHS Compliant



**Package Schematics**




**Notes:**

1. All dimensions are in millimeters (inches), Tolerance is  $\pm 0.25(0.01)$  unless otherwise noted.
2. Specifications are subject to change without notice.





Absolute Maximum Ratings ( $T_A=25^\circ\text{C}$ )	UR (GaAsP/ GaP)	UG (GaP)	Unit
Reverse Voltage Per Segment or (Dp and Comma)	$V_R$	5	5 V
Forward Current Per Segment or (Dp and Comma)	$I_F$	30	25 mA
Forward Current (Peak) Per Segment or (Dp and Comma) 1/10Duty Cycle 0.1ms Pulse Width	$i_{FS}$	160	140 mA
Power Dissipation Per Segment or (Dp and Comma)	$P_D$	150	125 mW
Operating Temperature	$T_A$	-40 ~ +85 $^\circ\text{C}$	
Storage Temperature	$T_{stg}$	-40 ~ +85 $^\circ\text{C}$	
Lead Solder Temperature [2mm Below Package Base]	260 $^\circ\text{C}$ For 3~5 Seconds		

Operating Characteristics ( $T_A=25^\circ\text{C}$ )	UR (GaAsP/GaP)	UG (GaP)	Unit
Forward Voltage (Typ.) Per Segment or (Dp and Comma) ( $I_F=10\text{mA}$ )	$V_F$	3.8	4 V
Forward Voltage (Max.) Per Segment or (Dp and Comma) ( $I_F=10\text{mA}$ )	$V_F$	5	5 V
Reverse Current (Max.) ( $V_R=5\text{V}$ )	$I_R$	10	10 $\mu\text{A}$
Wavelength of Peak Emission (Typ.) ( $I_F=10\text{mA}$ )	$\lambda_P$	627	565 nm
Wavelength of Dominant Emission (Typ.) ( $I_F=10\text{mA}$ )	$\lambda_D$	625	568 nm
Spectral Line Full Width At Half-Maximum (Typ.) ( $I_F=10\text{mA}$ )	$\Delta\lambda$	45	30 nm
Capacitance (Typ.) ( $V_F=0\text{V}$ , $f=1\text{MHz}$ )	$C$	15	15 pF





Part Number	Emitting Color	Emitting Material	Luminous Intensity ( $I_F=10\text{mA}$ ) ucd		Wavelength nm $\lambda_P$	Description
			min.	typ.		
XMURG100C-1A	Red	GaAsP/GaP	14000	25990	627	Column Cathode
	Green	GaP	21000	41990	565	




❖ UR



❖ UG



Wave Soldering Profile for Thru-Hole Products (Pb-Free Components)



- NOTES:
1. Recommend the wave temperature 245°C~260°C. The maximum soldering temperature should be less than 260°C.
  2. Do not apply stress on epoxy resins when temperature is over 85°C.
  3. The soldering profile apply to the lead free soldering (Sn/Cu/Ag alloy).
  4. During wave soldering, the PCB top-surface temperature should be kept below 105°C.
  5. No more than once.


Remarks:

If special sorting is required (e.g. binning based on forward voltage, luminous intensity / luminous flux, or wavelength), the typical accuracy of the sorting process is as follows:


1. Wavelength: +/-1nm
2. Luminous Intensity / Luminous Flux: +/-15%
3. Forward Voltage: +/-0.1V

Note: Accuracy may depend on the sorting parameters.

PACKING & LABEL SPECIFICATIONS



Inside LABEL On 1#BOX



Outside LABEL On Box

