
G15

15 kV

Make Only Load Switching RoHS Compliant, date code 0701 and later



ı	FEATURES
ı	 Excellent for capacitive discharge
ı	and safety dump switch application
ı	 Two mounting styles available,
ı	flange or through panel with jam n
ı	 Solder or threaded high voltage
ı	connections help make installation
П	


- User interchangeable coils provide for driver versatility
- Effectively bounce free operation

PRODUCT SPECIFICATIONS				
Contact & Relay Ratings	Units	G15		
Contact Form		С		
Contact Arrangement		SPDT		
Voltage, Test Max., Contacts & to Base (15 μA Leakage Max., dc or 60Hz)	kV Peak	17		
Voltage, Operating Max., Contacts & to Base (15 μΑ Leakage Max.)				
dc or 60 Hz	kV Peak	15		
2.5 MHz	kV Peak	-		
16 MHz	kV Peak	-		
32 MHz	kV Peak	-		
Current, Continuous Carry Max				
dc or 60 Hz	Amps	12		
2.5 MHz	Amps	-		
16 MHz	Amps	-		
32 MHz	Amps	-		
Coil Hi-Pot (V RMS, 60 Hz)	V	500		
Capacitance				
Across Open Contacts	pF	-		
Contacts to Ground	pF	-		
Resistance, Contact Max @ 1A, 28 Vdc	ohms	1.0		
Operate Time	ms	15		
Release Time	ms	9		
Life, Mechanical	cycles	1 million		
Weight, Nominal	g (oz)	84 (3)		
Vibration, Operating, Sine (55-500 Hz Peak)	G's	10		
Shock, Operating, 1/2 Sine11ms (Peak)	G's	50		
Temperature Ambient Operating	C	-55 to +125		

COIL RATINGS				
Nominal, Volts dc	12	26.5	115	
Pick-up, Volts dc, Max.	8	16	80	
Drop-Out, Volts dc	.5 - 5	1 - 10	5 - 50	
Coil Resistance (Ohms ±10%)	48	180	2900	

Ratings listed are for 25℃, sea level conditions

For more information, refer to Relay User Instructions



*Order the relay with the coil voltage in the part number as shown above. The coil voltage will appear on the coil plate near the coil terminals rather than in the P/N on the relay.

01/11/1

