

LS10 Ferrite Core Chip Inductors



Dimensions: $\frac{\text{Inches}}{(\text{mm})}$

Allied Part Number	Inductance (μh)	Tolerance (%)	Q Typ.	(L) Test Freq. (MHz)	SRF Min. (MHz)	DCR Max. (Ω)	IDC Current (mA)
LS10-1R2J-RC	1.20	5	55	7.9	350	0.50	1200
LS10-1R5J-RC	1.50	5	58	7.9	300	0.65	1200
LS10-1R8J-RC	1.80	5	54	7.9	280	0.75	1050
LS10-2R2J-RC	2.20	5	48	7.9	250	0.90	950
LS10-2R7J-RC	2.70	5	51	7.9	200	1.00	950
LS10-3R3J-RC	3.30	5	58	7.9	200	1.15	900
LS10-3R9J-RC	3.90	5	37	7.9	170	1.25	850
LS10-4R7J-RC	4.70	5	37	7.9	130	1.35	800
LS10-5R6J-RC	5.60	5	36	7.9	110	1.45	700
LS10-6R8J-RC	6.80	5	33	7.9	105	1.60	600
LS10-8R2J-RC	8.20	5	40	7.9	90	1.80	550
LS10-10J-RC	10.0	5	40	7.9	85	2.40	500
LS10-15J-RC	15.0	5	35	7.9	38	2.40	450

Available in tighter tolerances.
All specifications subject to change without notice.

Features

- 1008 SMD for Auto Insertion
Low DCR for Low Loss Applications
- Excellent Solderability Characteristics
- Highly resistant to mechanical forces
Excellent reliability in temperature and climate change

Electrical

Inductance Range: 1.2 μh to 15 μh
Tolerance: 5% across entire range.
Also available in 10% and 20%.

Operating Temp. Range: -25°C ~ 85°C

Test Equipment

Physical