





SMD SHIELDED POWER CHIP INDUCTOR

PCSV25

Dimensions: $\frac{\text{Inches}}{\text{(mm)}}$



Allied Part Number	Inductance (μh)	Tolerance (%)	Test Freq. MHz, 200mV	RDC (Ω) $\pm 30\%$	Isat (mA) Typ.	Irms (mA) Typ.	Marking
PCSV25-1R0M-RC	1.0	20	1	0.102	2800	2200	A
PCSV25-1R5M-RC	1.5	20	1	0.147	2100	1800	B
PCSV25-2R2M-RC	2.2	20	1	0.203	1780	1700	C
PCSV25-3R3M-RC	3.3	20	1	0.270	1320	1420	D
PCSV25-4R7M-RC	4.7	20	1	0.534	1100	1040	E
PCSV25-5R6M-RC	5.6	20	1	0.563	1060	1000	F
PCSV25-6R8M-RC	6.8	20	1	0.767	900	940	G
PCSV25-100M-RC	10	20	1	0.928	800	840	H
PCSV25-220M-RC	22	20	1	2.08	540	540	I

All specifications subject to change without notice.

Features

- Magnetically Shielded Construction
- Ultra Low Profile

Electrical

Inductance Range: 1.0 μh ~ 22 μh (other values being added)

Tolerance: Available in 20%

Operating Temp: -25°C ~ +105°C

Isat: Current at which the Inductance will drop by no more than 30% of its initial value.

Irms: Based on a temp rise of $\Delta T = 40^\circ\text{C}$ typical.

Resistance to Soldering Heat

Pre-Heat 150°C, 1 Min.

Solder Composition: Sn/Ag3.0/Cu0.5

Solder Temp: 260°C +/- 5°C for 10 sec

Test Equipment

(L): HP4287A + HP16197A

(RDC): Chroma MilliOhm Meter 16502

Current: HP4284A + HP42841A

Physical

Packaging: 2K per Tape and reel

Marking: As noted