





A-A



NOTES:
INSULATOR:LCP.COLOR-BLACK
USB CONTACT:BRASS 0.15MM THICKNESS,SELECTIVE GOLD
PLATED ON CONTACT AREA, GOLD FLASH PLATED
ON SOLDER TAIL,
80U" MIN NICKEL UNDERPLATED OVERALL,
SHELL:0.3MM THICKNESS ,FLASH
PLATED ON THE SOLDERING TAB.

REV	ECN.NO:	B Y	DATE
A0	NEW DWG	ING	10/06/02

Pin Number	Signal Name
1	VBUS
2	D-
3	D+
4	ID
5	GND
6	MicB_SSTX-
7	MicB_SSTX+
8	GND_DRAIN
9	MicB_SSRX-
10	MicB_SSRX+
Shell	Shield

-TOLERANCES- UNLESS OTHERWISE SPECIFIED				CnC Tech . LLC					
				APPD:		TITLE: MICRO USB 3.0-AB SMT			
X.X	±0.25	X.X°	±3.00°	CHECK:		DATE	SCALE	UNIT	PAGE
X.XX	±0.20	X.XX°	±1.00°	DRAW:		2010.06.02	FREE	MM	Z
X.XXX	±0.10	X.XXX°	±0.05°			PRODUCT NO: 1003-005-23100			1