

插頭部件 (Plug Component)			頭部剖皮尺寸 (Plug strip dimension)			線材規格(Wire Spec.)	尾部剖皮尺寸 (Terminal roj & Strip)			尾部處理 (Terminal Component)		
顏色(Color)	零件描述(Component)	數量(Q'ty)	內剝(Strip)	外剝(Roj)	顏色(Color)		外剝(Roj)	內剝(Strip)	顏色(Color)	零件描述(Component)	顏色(Color)	數量(Q'ty)
35P透明 90A±2A Clear	FM-2 (15A 125V-) (NEMA5-15P)	1	10±1	60±2	黑/Black(L)	SJT 14AWG/3C 105°C 灰色(Gray)	15±1	5 ⁺¹ ₋₀	黑/Black(L)	ME-302 (15A 125V-) (IEC 320 C13)	35P透明 90A±2A Clear	1
鍍鎳 Nickel-Plated	□4.75 U型開關	1	10±1	60±2	白/White(N)	線長: (Length) 1866.9 ^{+50.8} _{-12.7}	15±1	5 ⁺¹ ₋₀	白/White(N)	電腦電源線端子 (Computer power cord terminals)	銅本色(Copper)	3
鍍鎳 Nickel-Plated	6.3±1.5 單片圓頭端子 (Solid Blades)	2	20±1	75±2	綠/Green(E)		15±1	5 ⁺¹ ₋₀	綠/Green(E)	302兩件式內模 (302 Inner Body)	白色(White)	1
鍍鎳 Nickel-Plated	墊片 (Gasket)	3										

1828.8^{+50.8}_{-12.7}

15±0.15

插頭端面圖
(Dimensions of Plug Face)

插頭端面圖
(Dimensions of Plug Face)

線材截面圖
(Wire Cross-Section)

Insulation Thickness 0.76 mm
Overall Diameter 3.45±0.10 mm
Copper Conductor
41/0.254±0.004 mm
Resistance 8.88
(20°C (Max). ohms/km)
Jacket Thickness 0.76mm
Overall Diameter 9.3±0.15mm

包裝方式(Packing)

扎線方式 (Bulk Pack)	每 10 條一扎 Per 10 pcs/Ties
紙箱尺寸 (Carton Size)	480 X 320 X
包裝數量 (Packing Q'ty)	PCS
標籤(Label)	UL Detachable Label
正側事項 (Carton Print)	依客戶要求印刷 (See Purchase Order)

電線印字內容
Wire Printed

使用充實 線材 凹印字
(Un-Filler, Gravure)

紙箱事項標碼
Shipping Mark

1. 高壓測試:1500V/1Sec <1mA
(Hi-Pot Test:1500v/1Sec <1mA)

電線印字內容
Wire Printed

使用充實 線材 凹印字
(Un-Filler, Gravure)

紙箱事項標碼
Shipping Mark

CSA SJT 14AWG(2.08mm²)x3C FT2 105°C 300V E77975 WONDERFUL-D
UL SJT 14AWG(2.08mm²)x3C FT2 105°C 300V -LF-
UL SJT 14AWG(2.08mm²)x3C FT2 105°C 300V -LF-
CSA SJT 14AWG(2.08mm²)x3C FT2 105°C 300V LL43774 -F- -LF-

SIZE: A4
UNIT: mm
SCALE: 1:1
PROJ.

SIGNATURE NAME DATE
APPROVED
M.F.G. CHECKED
Q.A. CHECKED
DRAWN 楊承正 2011/11/28
CUSTOMER

2011 1128 新版發行 楊承正
REV DATE DESCRIPTION SYMBOL
PART No. 800-14-00D-GR-0006F
DWG No.

CnC Tech, LLC
Industrial Cable and Connector Technology