


插頭部件 (Plug Component)			頭部製皮尺寸 (Plug strip dimension)			線材規格(Wire Spec.)	尾部製皮尺寸 (Terminal roj & Strip)			尾部處理 (Terminal Component)		
顏色(Color)	零件描述(Component)	數量 (Qty)	內制(Strip)	外制(Roj)	顏色(Color)	SJT 18AWG/3C 105°C 黑色(Black) 線長: (Length) 1841.5 ^{+50.8} _{-12.7}	外制(Roj)	內制(Strip)	顏色(Color)	零件描述(Component)	顏色(Color)	數量 (Qty)
35P透明 90A±2A Clear	FM-2 (10A 125V-) (NEMA5-15P)	1	10±1	60±2	黑/Black(L)		15±1	5 ⁺¹ ₋₀	黑/Black(L)	ME-302 (10A 125V-) (IEC 320 C13)	35P透明 90A±2A Clear	1
鍍鎳 Nickel-Plated	4.75 U型開管 4.75 Grounding	1	10±1	60±2	白/White(N)		15±1	5 ⁺¹ ₋₀	白/White(N)	電腦電源線端子 Computer power cord terminals	銅本色(Copper)	3
鍍鎳 Nickel-Plated	6.3*1.5 單片圓頭端子 (Solid Blades)	2	20±1	75±2	綠/Green(E)		15±1	5 ⁺¹ ₋₀	綠/Green(E)	302兩件式內模 (302 Inner Body)	白色(White)	1
鍍鎳 Nickel-Plated	墊片 (Gasket)	3										




插頭端面圖
(Dimensions of Plug Face)

插頭端面圖
(Dimensions of Plug Face)

Insulation Thickness 0.76 mm
Overall Diameter 2.70±0.10 mm

Copper Conductor
41/0.160±0.004 mm
Resistance 22.4
(20°C Max), ohms/km

Jacket Thickness 0.76mm
Overall Diameter 7.8±0.15mm



線材截面圖
(Wire Cross-Section)

包裝方式(Packing)		
扎線方式 (Bulk Pack)	每 10 條一扎 Per 10 pcs/Ties	
紙箱尺寸 (Carton Size)	480 X 320 X	
包裝數量 (Packing Qty)	PCS	
標籤(Label)	UL Detachable Label	
正側字樣 (Carton Print)	依客戶要求印刷 (See Purchase Order)	
電線印字內容 Wire Printed	使用充實 線材 四印字 (Un-Filler, Gravure)	紙箱字樣標記 Shipping Mark
V E322763 (UL) SJT 18AWG(0.824mm')x3C VW-1 105°C 300V /T c(UL) SJT 18AWG(0.824mm')x3C FT2 105°C 300V -1F- (UL) SJT 18AWG(0.824mm')x3C VW-1 105°C 300V E77975 WONDERFUL D CSA SJT 18AWG(0.824mm')x3C FT2 105°C 300V LL43774 -F- -1F-		



SIZE: A4
UNIT: mm
SCALE: 1:1
PROJ.

SIGNATURE	NAME	DATE			
APPROVED					
M.F.G. CHECKED			2011 1128	新版發行	楊承正
Q.A. CHECKED			REV DATE	DESCRIPTION	SYMBOL
DRAWN	楊承正	2011/11/28	PART No.	800-18-00D-BL-0006F	
CUSTOMER			DWG No.		
CnC Tech, LLC Industrial Cable and Connector Technology					