

插頭部件 (Plug Component)			頭部剖皮尺寸 (Plug strip dimension)			線材規格(Wire Spec.)		尾部剖皮尺寸 (Terminal roj & Strip)			尾部處理 (Terminal Component)		
顏色(Color)	零件描述(Component)	數量(Q'ty)	內剝(Strip)	外剝(Roj)	顏色(Color)	SJT 18AWG/3C 105°C 紅色(Red) 線長: (Length) 1828.8 ^{+50.8} _{-12.7}		外剝(Roj)	內剝(Strip)	顏色(Color)	顏色(Color)	零件描述(Component)	數量(Q'ty)
35P紅色 90A+2A Red 鍍鎳 Nickel-Plated	ME-301 (10A 125V-) (NEMA 5-15P) Ø4.75 圓管端子 (Earth Pin Terminal)	1	5 ⁺¹ ₋₀	23±1	黑/Black(L)			16±1	5 ⁺¹ ₋₀	黑/Black(L)	35P紅色 90A+2A Red 銅本色 (Copper)	ME-302 (10A 125V-) (IEC 320 C-13) 電腦電源線端子 GEM#98745BS-0 Computer power cord terminals	1
鍍鎳 Nickel-Plated	6.3*1.5 單片圓頭端子 (Solid Blades)	2	5 ⁺¹ ₋₀	23±1	白/White(N)			16±1	5 ⁺¹ ₋₀	白/White(N)	白色(White)	ME-302兩件式內模 (ME-302 Inner Body)	3
白色(White)	301單件式內模 (301 Inner Body)	1			綠/Green(E)			16±1	5 ⁺¹ ₋₀	綠/Green(E)	白色(White)		1

Earth Ground (Green)
Ø4.75±0.15

白/White(N) 黑/Black(L)

12.7±0.15

插頭端面圖
(Dimensions of Plug Face)

15±0.15

插頭端面圖
(Dimensions of Plug Face)

1828.8^{+50.8}_{-12.7}

線材剖面圖
(Wire Cross-Section)

Insulation Thickness 0.76 mm
Overall Diameter 2.7±0.10 mm

Copper Conductor
41/0.160±0.004 mm
Resistance 22.4
(20°C (Max), ohms/km)

Jacket Thickness 0.76 mm
Overall Diameter 7.8±0.15 mm

包裝方式(Packing)

扎線方式 (Bulk Pack)	每 10 條一扎 Per 10 pcs/Ties
紙箱尺寸 (Carton Size)	480 X 320 X 250
包裝數量 (Packing Q'ty)	PCS
標籤(Label)	UL Detachable Label
正側標頭 (Carton Print)	依客戶要求印刷 (See Purchase Order)

1. 高壓測試:1500V/1Sec <1mA
(Hi-Pot Test:1500v/1Sec <1mA)

電線印字內容
Wire Printed

使用充實線材 凹印字
(Un-Filler, Gravure)

紙箱標頭標碼
Shipping Mark

CSA SJT 18AWG(0.824mm)*x3C FT2 105°C 300V
/UL c(UL) SJT 18AWG(0.824mm)*x3C FT2 105°C 300V -LF-
(UL) SJT 18AWG(0.824mm)*x3C VW-1 105°C 300V E77975 WONDERFUL-D
CSA SJT 18AWG(0.824mm)*x3C FT2 105°C 300V 1143774 -F- -LF-

SIZE: A4
UNIT: mm
SCALE: 1:1
PROJ.

SIGNATURE	NAME	DATE
APPROVED		
M.F.G. CHECKED		
Q.A. CHECKED		
DRAWN	楊承正	2011.11.21

2011 1121	新版發行	楊承正
REV DATE	DESCRIPTION	SYMBOL
PART No.	800-18-13D-RE-0006F	
DWG No.		

CnC Tech, LLC
Industrial Cable and Connector Technology