



SPECIFICATIONS AND OPTIONAL FEATURES

<u>TYPE</u>	<u>CIRCUIT</u>	<u>ELECTRICAL RATING</u>	<u>UL & CSA</u>
G-107-SI-0511	SPDT	.5A AC DC 125V	APPROVED

BUTTON OPTIONS

<u>LENGTH</u>	<u>PART NUMBER</u>	<u>COLOR</u>
.140 (3.56mm)	G-02-240-1 is Standard	BLACK
.200 (5.08mm)	G-02-240-2	BLACK
.250 (6.35mm)	G-02-240-3	BLACK
.250 (6.35mm)	G-02-240-4	BLue
.250 (6.35mm)	G-02-240-5	Red

TERMINALS

Standard solder terminal also mates with AMP connector 62343-1.

MOUNTING

Snaps directly into panel having hole piercing as shown.
Designed for panel thickness of .047, .062, .078 and .093.

REVISIONS

REVISIONS	DATE	DESCRIPTION
0		
1		

RELEASED 1-8-85 GZ
.360±.010 WAS .400±.010 AND 9.14±.25 WAS 10.16±.25.
NM 7-24-85
JUL. 28.1986

PDF File Made	ew INDUSTRIES Southampton, Pa. 18966		Title: SNAP-IN SLIDE SWIDGET JR. ASSEMBLY S.P. - D.T.
	TOLERANCES UNLESS OTHERWISE SPECIFIED		
	2 Place decimal ±.010 3 Place decimal ±.005 Angles ± 1°	METRIC 1 Place dec. ±.25mm 2 Place dec. ±.13mm	Division: SWITCH
	Made for: CW		
	Drawn by: B.DeRosier 1-4-85		
Checked by: CH 1-7-85		Dwg. No. G-107-SI-0511	
Approval: GZ 1-8-85			