



NOTES:

1. MAX ALLOWABLE BOW: .005 INCH/INCH.
2. HEIGHT VARIATION BETWEEN ANY TWO PINS SHALL BE .010 MAX.
3. TERMINAL PUSHOUT FORCE: 2 lbs. MIN.
4. MAX PIN ROTATION IN BODY: 2°.
5. ϕ REPRESENTS A CRITICAL DIMENSION.
6. FOR -S, -G & -L PLATING, GOLD WILL BE ON CONTACT AREA.
7. TUBE POSITIONS -07 THRU -50. POSITIONS -01 THRU -06 ARE TO BE LAYER PACKAGED.
8. MAX CUT FLASH: .010
9. FOR -D, USE DWM-50-D WHEN RAN ON BOARD STACKER AUTOMATION, HTMS-50-D FOR ALL OTHER PROCESSES. FOR -S, USE HTMS-50-S.

SEE NOTE 7

TABLE 1

LEAD STYLE	TERMINAL SPEC.	'L'	CONTACT AREA	BOARD SPACE MAX (REF)	PACKAGING (7 POS MIN).					
					SINGLE ROW			DOUBLE ROW		
-01	T-1M6-18-XX-2	.450 [11.43]	.190 [4.83]	REF	.330 [8.38]	PT-1-24-02-03 (2)	TP-24	PT-1-24-01-51 (2)	TP-13	
-51	T-1M6-02-XX-2	.410 [10.41]	.140 [3.56]	REF	.290 [7.37]	PT-1-24-02-03 (2)	TP-24	PT-1-24-01-22 (2)	TP-03	
-52	T-1M6-12-XX-2	.425 [10.80]	.165 [4.19]	REF	.305 [7.75]	PT-1-24-02-03 (2)	TP-24	PT-1-24-02-53 (2)	TP-09	
-53	T-1M6-04-XX-2	.505 [12.83]	.190 [4.83]	REF	.385 [8.78]	PT-1-24-02-03 (2)	TP-24	PT-1-24-02-46 (2)	TP-03	
-54	T-1M6-14-XX-2	.555 [17.10]	.190 [4.83]	REF	.435 [11.05]	PT-1-24-02-03 (2)	TP-24	PT-1-24-06-29 (2)	TP-03	
-55	T-1M6-03-XX-2	.610 [15.49]	.190 [4.83]	REF	.490 [12.45]	PT-1-24-02-03 (2)	TP-24	PT-1-24-04-44 (2)	TP-03	
-56	T-1M6-13-XX-2	.625 [15.88]	.190 [4.83]	REF	.505 [12.83]	PT-1-24-10-03 (2)	TP-24	PT-1-24-02-25 (2)	TP-03	
-57	T-1M6-19-XX-2	.650 [16.51]	.190 [4.83]	REF	.530 [13.46]	PT-1-24-10-03 (2)	TP-24	PT-FW004-0X-D-EX (2)	TP-24	
-58	T-1M6-05-XX-2	.705 [17.91]	.190 [4.83]	REF	.585 [14.86]	PT-1-24-10-03 (2)	TP-24	PT-1-24-01-51 (2)	TP-13	
-59	T-1M6-15-XX-2	.755 [19.18]	.190 [4.83]	REF	.635 [16.13]	PT-1-24-10-03 (2)	TP-24	PT-FW004-0X-D-EX (2)	TP-24	
-60	T-1M6-16-XX-2	.825 [20.96]	.190 [4.83]	REF	.705 [17.91]	PT-1-24-10-03 (2)	TP-24	PT-1-24-01-71 (2)	TP-03	
-61	T-1M6-28-XX-2	1.050 [26.67]	.190 [4.83]	REF	.930 [23.62]	PT-1-24-02-04 (2)	TP-33	PT-1-24-08-03 (2)	TP-07	



MATERIAL:
INSULATOR:
BLACK LIQUID CRYSTAL POLYMER OR
NYLON 4/6

TERMINAL:
PHOSPHOR BRONZE

DWM-XX-XX-XX-X-XXX-XXX

BODY LENGTH SPEC
EXPRESSED IN # POS PER ROW
(-01 THRU -50)
"XX" = No. OF POS x .050

LEAD STYLE
SEE TABLE 1


PLATING SPECIFICATION

-G: GOLD, SPECIFY -G IN TERMINAL SUFFIX -X
-T: TIN, SPECIFY -T IN TERMINAL SUFFIX -X
ONLY AVAILABLE ON LEAD STYLES -01, -51 AND -52.
-S: SELECTIVE, SPECIFY -S IN TERMINAL SUFFIX -X
-TM: TIN, SPECIFY -T IN TERMINAL SUFFIX -X
ONLY AVAILABLE ON LEAD STYLES -01, -51 AND -52.
-SM: MATTE SELECTIVE, SPECIFY -S IN TERMINAL SUFFIX -X
-L: LIGHT SELECTIVE GOLD, MATTE TIN TAIL, SPECIFY -L IN TERMINAL SUFFIX (SEE NOTE 6)

TITLE:
BOARD SPACING
MICRO STRIPS

DWG NO:
DWM-XX-XX-XX-X-XXX-XXX
SHEET 1 OF 1

FIG. 1



PROPRIETARY NOTE
THIS DOCUMENT CONTAINS INFORMATION
CONSIDERED TO BE PROPRIETARY TO
SANTEC INC. AND IS NOT TO BE
REPRODUCED OR TRANSMITTED IN
ANY FORM OR BY ANY MEANS, ELECTRONIC
OR MECHANICAL, INCLUDING PHOTOCOPYING,
RECORDING, OR BY ANY INFORMATION
SYSTEM WITHOUT THE WRITTEN
CONSENT OF SANTEC INC.

MADE BY:
GREG REIDINGER S-9-91
CHECKED BY: MCCARTIN

DATE:
APPROVAL
DEM

santec

520 PARK EAST BLVD. NEW ALBANY, INDIANA 47150
PHONE (812) 944-6733 P.O. BOX 1147
CODE 55322

DWM-XX-XX-XX-X-XXX-XXX
SHEET 1 OF 1