samtec

mini MATE®

(2,54 mm) .100"



IPS1 SERIES

SHROUDED POWER CONNECTOR SET

SPECIFICATIONS

For complete specifications see www.samtec.com?IPS1

Insulator Material:
Black LCP
Contact Material:
Phosphor Bronze
Plating:
Sn or Au over
50µ" (1,27 µm) Ni
Operating Temp Range:
-55°C to +105°C with Tin;
-55°C to +125°C with Gold
Insertion Depth:
(3,81 mm) .150" to
(6,48 mm) .255"
Wiping Distance:
(0,38 mm) .015"
Insertion Force (SMT):
3.0 oz (0,83 N) avg.
Withdrawal Force (SMT):
2.6 oz (0,72 N) avg.
Insertion Force (T/H):
6.0 oz (1,67 N) avg.
Withdrawal Force (T/H):
5.0 oz (1,39 N) avg.
Voltage Rating:
550 VAC/777 VDC
RoHS Compliant:
Yes

Processing:

Lead–Free Solderable:
Yes
SMT Lead Coplanarity:
(0,13 mm) .005" max (05-10)
(0,15 mm) .006" max (15-25)

Mates with:
IPT1

TIGER BUY CONTACT™

IPT1/IPS1	
PINS	CURRENT RATING (PER CONTACT)
1	5.9 A
2	4.8 A
3	4.1 A
4	3.6 A
ALL	2.3 A



RUGGEDIZED by SAMTEC

- Individually shrouded contacts
- Locking clip option

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality

FILE NO. E111594

ALSO AVAILABLE
(MOQ Required)

- Other sizes
- Other platings
- Latching feature
- No. 1 position polarized

Contact Samtec.

Note:
Some sizes, styles and options are non-standard, non-returnable.

IPS1	–	1	NO. PINS PER ROW	–	01	–	PLATING OPTION	–	D	–	TAIL OPTION	–	OTHER OPTION

05, 10, 15, 20, 25
(Standard sizes)

–L
= 10µ" (0,25 µm) Gold on contact, Matte Tin on tail

Leave blank for Through-hole

–VS
= Surface Mount

–RA
= Right Angle

–LC
= Locking Clip (Manual placement required) (–VS only)

–K
= (5,50 mm) .217" DIA Polyimide film Pick & Place Pad (–VS only)

–TR
= Tape & Reel Packaging (–VS only)





Due to technical progress, all designs, specifications and components are subject to change without notice.

SAMTEC USA • Tel: +1-800-SAMTEC-9 or +1-812-944-6733 **SAMTEC NORTHERN CALIFORNIA** • Tel: +1-408-395-5900 **SAMTEC SOUTHERN CALIFORNIA** • Tel: +1-800-726-8329
SAMTEC SOUTH AMERICA • Tel: +55 31 3786 3227 **SAMTEC UNITED KINGDOM** • Tel: +44 01236 739292 **SAMTEC GERMANY** • Tel: +49 (0) 89 / 89460-0
SAMTEC FRANCE • Tel: +33 1 60 95 06 60 **SAMTEC ITALY** • Tel: +39 039 6890337 **SAMTEC NORDIC/BALTIC** • Tel: +46 8 4477280 **SAMTEC BENELUX** • Tel: +44 01236 739292
SAMTEC ISRAEL • Tel: +972 3 7526600 **SAMTEC INDIA** • Tel: +91 80 3272 1612 **SAMTEC ANZ** • Tel: +613 9580 0683 **SAMTEC SINGAPORE** • Tel: +65 6745 5955 **SAMTEC JAPAN** • Tel: +81 45 475 1385
SAMTEC SHANGHAI • Tel: +86 21 6083 3766 **SAMTEC SHENZHEN** • Tel: +86 755 83776780 **SAMTEC TAIWAN** • Tel: +886 2 2735 6109 **SAMTEC HONG KONG** • Tel: +852 26904858 **SAMTEC KOREA** • Tel: +82 31 717 5685