


## Chroma amplifier transistor

## 2SC4061K

## ■ Features

- High breakdown voltage.
- Low collector output capacitance.
- Ideal for chroma circuit.

■ Absolute Maximum Ratings  $T_a = 25^\circ\text{C}$ 

Parameter	Symbol	Rating	Unit
Collector-base voltage	$V_{CB0}$	300	V
Collector-emitter voltage	$V_{CE0}$	300	V
Emitter-base voltage	$V_{EB0}$	5	V
Collector current	$I_C$	100	mA
Collector power dissipation	$P_C$	0.2	W
Junction temperature	$T_j$	150	$^\circ\text{C}$
Storage temperature	$T_{stg}$	-55 to +150	$^\circ\text{C}$

■ Electrical Characteristics  $T_a = 25^\circ\text{C}$ 

Parameter	Symbol	Testconditions	Min	Typ	Max	Unit
Collector-base breakdown voltage	$BV_{CB0}$	$I_C=50\mu\text{A}$	300			V
Collector-emitter breakdown voltage	$BV_{CE0}$	$I_C=100\mu\text{A}$	300			V
Emitter-base breakdown voltage	$BV_{EB0}$	$I_E=50\mu\text{A}$	5			V
Collector cutoff current	$I_{CBO}$	$V_{CB}=200\text{V}$			0.5	$\mu\text{A}$
Emitter cutoff current	$I_{EBO}$	$V_{EB}=4\text{V}$			0.5	$\mu\text{A}$
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C=50\text{mA}, I_B=5\text{mA}$			2	V
DC current transfer ratio	$h_{FE}$	$V_{CE}=10\text{V}, I_C=10\text{mA}$	56		180	
Output capacitance	$f_T$	$V_{CE}=30\text{V}, I_E=-10\text{mA}, f=30\text{MHz}$	50	100		MHz
Transition frequency	$C_{ob}$	$V_{CB}=30\text{V}, I_E=0\text{A}, f=1\text{MHz}$		3		pF

■  $h_{FE}$  Classification

Marking	ANN	ANP
Rank	N	P
$h_{FE}$	56 ~ 120	82 ~ 180