


High-frequency Amplifier Transistor

2SC4618

Features

Low collector capacitance.

Low rbb, high gain, and excellent noise characteristics.

Absolute Maximum Ratings $T_a = 25^\circ\text{C}$

Parameter	Symbol	Rating	Unit
Collector-base voltage	V_{CB0}	40	V
Collector-emitter voltage	V_{CEO}	25	V
Emitter-base voltage	V_{EBO}	5	V
Collector current	I_c	50	mA
Collector power dissipation	P_C	0.15	W
Junction temperature	T_j	150	$^\circ\text{C}$
Storage temperature	T_{stg}	-55 to +150	$^\circ\text{C}$

Electrical Characteristics $T_a = 25^\circ\text{C}$

Parameter	Symbol	Test conditons	Min	Typ	Max	Unit
Collector-base breakdown voltage	BV_{CB0}	$I_c=50\mu\text{A}$	40			V
Collector-emitter breakdown voltage	BV_{CEO}	$I_c=1\text{mA}$	25			V
Emitter-base breakdown voltage	BV_{EBO}	$I_E=50\mu\text{A}$	5			V
Collector cutoff current	I_{CBO}	$V_{CB}=24\text{V}$			0.5	μA
Emitter cutoff current	I_{EBO}	$V_{EB}=3\text{V}$			0.5	μA
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_c/I_B=10\text{mA}/1\text{mA}$			0.3	V
DC current gain	h_{FE}	$V_{CE}=6\text{V}, I_c=1\text{mA}$	82		180	
Transition frequency	f_T	$V_{CE}=6\text{V}, I_E=-1\text{mA}, f=100\text{MHz}$		300		MHz
Output capacitance	C_{ob}	$V_{CE}=6\text{V}, I_E=0\text{A}, f=1\text{MHz}$		1.3	2.2	pF

Marking

Marking	AN	AP	AQ