


## NPN General Purpose Transistors

## BCW71,BCW72

## ■ Features

- Low current (max. 100 mA).
- Low voltage (max. 45 V).
- Low noise.

■ Absolute Maximum Ratings  $T_a = 25^\circ\text{C}$ 

Parameter	Symbol	Rating	Unit
Collector-base voltage	$V_{CB0}$	50	V
Collector-emitter voltage	$V_{CE0}$	45	V
Emitter-base voltage	$V_{EB0}$	5	V
Collector current	$I_C$	100	mA
Peak collector current	$I_{CM}$	200	mA
Peak base current	$I_{BM}$	200	mA
Total power dissipation	$P_{tot}$	250	mW
Storage temperature	$T_{stg}$	-65 to +150	$^\circ\text{C}$
Junction temperature	$T_j$	150	$^\circ\text{C}$
Operating ambient temperature	$R_{amb}$	-65 to +150	$^\circ\text{C}$
Thermal resistance from junction to ambient *	$R_{th\ j-a}$	500	K/W

\* Transistor mounted on an FR4 printed-circuit board.

**BCW71,BCW72**■ Electrical Characteristics  $T_a = 25^\circ\text{C}$ 

Parameter	Symbol	Testconditions	Min	Typ	Max	Unit
Collector cutoff current	ICBO	$I_E = 0; V_{CB} = 20\text{ V}$			100	nA
	ICBO	$I_E = 0; V_{CB} = 20\text{ V}; T_j = 100^\circ\text{C}$			10	$\mu\text{A}$
Emitter cutoff current	IEBO	$I_C = 0; V_{EB} = 5\text{ V}$			100	$\mu\text{A}$
DC current gain	BCW71	$I_C = 10\ \mu\text{A}; V_{CE} = 5\text{ V}$		90		
	BCW72			150		
DC current gain	BCW71	$I_C = 2\text{ mA}; V_{CE} = 5\text{ V}$	110		120	
	BCW72		200		450	
Collector-emitter saturation voltage	$V_{CE(sat)}$	$I_C = 10\text{ mA}; I_B = 0.5\text{ mA}$		120	250	mV
		$I_C = 50\text{ mA}; I_B = 2.5\text{ mA}$		210		mV
Base to emitter saturation voltage	$V_{BE(sat)}$	$I_C = 10\text{ mA}; I_B = 0.5\text{ mA}$		750		mV
		$I_C = 50\text{ mA}; I_B = 2.5\text{ mA}$		850		mV
Base to emitter voltage	$V_{BE}$	$I_C = 2\text{ mA}; V_{CE} = 5\text{ V}$	550		700	mV
Collector capacitance	$C_c$	$I_E = I_C = 0; V_{CB} = 10\text{ V}; f = 1\text{ MHz}$		2.5		pF
Transition frequency	$f_T$	$I_C = 10\text{ mA}; V_{CE} = 5\text{ V}; f = 100\text{ MHz}$	100			MHz
Noise figure	NF	$I_C = 200\ \mu\text{A}; V_{CE} = 5\text{ V}; R_s = 2\text{ k}\Omega;$ $f = 1\text{ kHz}; B = 200\text{ Hz}$			10	dB

## ■ hFE Classification

TYPE	BCW71	BCW72
Marking	K1	K2