


GU256X64C-7000

SIMPLIFIED DATASHEET

■ Features

256x64 dot compact, high resolution display.
 Suitable for embedding in devices where wide space is not available.

■ Physical dimension



() : Reference only
 Unit : mm

Get full specification



Click here to go to request form.

Specifications

■ Electrical Ratings

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Power supply voltage	VCC	4.75	5.00	5.25	VDC	-

■ Electrical Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
'L' Logic Input Current D0-D7 /WR/ RD /RESET	IIL1 IIL2	-	-	-0.15 -0.6	mA	VIN=0V
'H' Logic Input Current D0-D7 /WR/ RD /RESET	IIH	-	-	1.0	μ ADC	VIN=5V
Logic Input Voltage	VIH	0.8VCC	-	VCC	VDC	-
D0-D7 /WR/ RD /RESET	VIL	0	-	0.2VCC	VDC	-
Logic Output Voltage	VOH	3.8	-	VCC	VDC	IOH=-1.5mA
D7(Busy flag), PBUSY	VOL	0	-	0.6	VDC	IOL=1.6mA
Logic input resistance	RIN	3	-	-	K Ω	-
Logic Input Voltage	VIH	3.0	-	+1.5	VDC	-
SIN	VIL	-15	-	0.5	VDC	-
Logic Output Voltage	VOH	4.0	-	VCC	VDC	RL=3K Ω
SBUSY	VOL	0	-	0.5	VDC	RL=3K Ω
Power Supply Current 1	ICC-1	-	0.43	0.54	ADC	All dots ON
Power Supply Current 2	ICC-2	-	0.32	0.4	ADC	All dots OFF
Power Supply Current 3	ICC-3	-	47	57	mADC	Display power OFF
Power Consumption		-	2.15	2.70	W	All dots ON

■ Optical Specifications

Parameter	
Number of Dots	16,384 (256 x 64)
Character numbers	36 x 8 / Max42 x 8 by 5 x 7 dot ANK
Display Area	83.08 mm x 20.68 mm
Dot Size (X x Y)	0.20 mm x 0.20 mm
Dot Pitch (X x Y)	0.325 mm x 0.325 mm
Luminance	350 cd/m ² Min. (700 cd/m ² Typ.)
Color of illumination	Green (Blue-Green)

■ Environmental Specifications

Parameter	
Operating Temperature	-40 ~ +85 degrees celsius
Storage Temperature	-40 ~ +85 degrees celsius
Operating Humidity	20 ~ 80% R.H. (non-condensing)
Storage Humidity	20 ~ 80% R.H. (non-condensing)
Vibration (non-operating)	10-55-10Hz, all amplitude 1mm, 30 minutes, X-Y-Z
Shock (non-operating)	392m/s ² (40G) 9ms X-Y-Z, 3 times each direction

■ Character display

Parameter	
Number of Dots	256 x 64 dots
Character font type	5 x 7 ANK, International font
Character width	Fixed/Proportional character format 1&2
Attribution	Character magnify, Reverse
Weight	About 59 g

■ Interface

Parallel(CMOS), Asynchronous Serial (RS232)

■ Pin Assignment (Parallel)

Pin No.	Signal	Pin No.	Signal
1	GND	2	Vcc
3	NC	4	RS
5	/WR	6	/RD
7	D0	8	D1
9	D2	10	D3
11	D4	12	D5
13	D6	14	D7(PBUSY)

(Asynchronous Serial)

Pin No.	Signal	Baud Rate Setting
1	Vcc	9600bps
2	SIN	19200bps
3	GND	38400bps*
4	SBUSY	115200bps
5	NC	(*:Default setting)
6	/RESET	

■ Functions

Parameter	
Control command	
Scroll display action	
Proportional Font function	
User-Windows function	
AND/OR/XOR Mixture display	
Reverse display	
Bit image display	
Character download function	
etc.	



Leaflet contents, and specifications and external appearance of products, may change without notice.

Please confirm product details in the specification.

(C)Copyright NORITAKE ITRON CORP.