

PAR-2192M

PAR-2192M features an **Intel® D510 Dual-Core** 1.6GHz processor. This fanless embedded system supports GSM/GPRS/WCDMA/HSDPA and GPS.

Specifications

Fanless Platform	Low power, low operation temperature Fanless aluminum alloy embedded system
Dimensions	208mm (W) X 115 mm (H) X 230mm (D)
Processor	Intel® Atom Dual-core D510 1.6 GHz low power processor 512KB L2 Cache, supports 64 bit, HT, XD technology Built-in media grade high performance Graphic engine
Chipset	Intel® ICH 8-M South Bridge Chipset
Memory	On board 512MB + 1 SO-DIMM Socket, up to 2.5 GB without ECC, 667 MHz DDR 2 Memory
BIOS	Phoenix BIOS, Support Console Redirection & Power On After Power failure
Power Management	S3, S4 suspend mode Low power protection design for boot-up and shutdown µP detection ignition status for 8 level power ON/OFF delay
3.5G Mobile Wireless	Sierra MC8790V, Supports GSM/GPRS/EDGE/WCDMA/HSDPA, flexible tri-band or quadband
GPS Support	SiRF-3 high sensitivity GPS, 20 channel tracking
DVR Function	4 channel NTSC/PAL H.264 120/100 fps @ D1 DVR function SDK support VC++ / NET / BCB / VB / V4L2
Disk Drive Storage	1 Removable HDD with Anti-vibration, 1 internal SATA HDD
Expansion	1 internal SATA H, 1 Mini PCI, 1 Mini PCIe, 1 PCI-32
Ethernet	1 Realtek 8111 100/1000 Mbps LAN interface with Wake-On-LAN & DMI
Watchdog Timer	Programmable WDT from 1 to 255 seconds
Display Function	VGA, 18-bit dual channel LVDS
Hardware Monitor	Monitors voltage and temperature
Audio	ALC655 Codec
Smart Battery Interface	5000 mAh Smart Battery Kit
RS-232/485	2 DB-9 RS-232/485, 1 DB-9 RS-232, all optional DC output
Isolated Digital I/O	2500V isolation protection 3D-In: Low Level: 0-3V, High Level: 10-50V 2D-Out: 500mA drive capability
Isolated CAN	CAN 2.0B provide by dedicate MCU, Speed up to 921Kbps
Front Panel Extend I/O	1 power button, 1 GPRS/GPS power ON/OFF switch, 1 USB, 2 system status LED, 1 GPRS power LED, 6 GPRS LEDs (3 speed mode/3 signal status), 1 SIM card socket, 5 SMA type Antennas (HSDPA/GPS/WLAN), 1 removable 2.5" SATA HDD
Rear Panel Extend I/O	Screw-Lock DC power input, 3-pin connector, 2 DB-9 RS-232/485, 1 DB-9 for Digital-IO & Ignition status, 1 DB-15 VGA, 1 CAN Bus, 4 USB, 1 x 100/1000 Mbit LAN connector, 1 DB-15 VGA connector, 2 DVI connector for 4 channel DVR Video and Audio input, 1 Micro-phone-in, 1 Speaker-out, Power LED, HDD LED, 1 Power button
Power Supply	DC 6V-34V / 1.5-5 A input (Optional DC 6V-80V)
Power ON/OFF Mode	AT or ATX Power ON/OFF mode
Environment	Operation Temperature: -30°C to 50°C (-22°F to 122°F) Storage Temperature: -40°C to 80°C (-40°F to 176°F) Relative Humidity: 10% to 90% (Non-condensing) Vibration: 2G @ 5-500Hz random with CF, SSD & HDD
OS Support	Windows XP Professional / Embedded, Windows 7, Linux
Certification	CE Class A, FCC Class A, E13 Mark
Technical Support	Free technical support

Product Name: PAR-2192M / Pipal 2192M
Part Number: PAR-2192M



FEATURES

- ✓ *Intel® Dual-core D510 1.6 GHz Processor*
- ✓ *Supports GSM / GPRS / HSDPA / GPS and ignition power control*
- ✓ *DDR-2 667MHz, On board 512MB + SO-DIMM, up to 2.5 GB without ECC*
- ✓ *1 PCI-32, 1 Mini PCI, 1 Mini PCIe slot*
- ✓ *DC 6V to 34V power input, up to DC 80V*
- ✓ *Isolated Digital I/O and CAN 2.0B*

Connect Tech Inc.

42 Arrow Road, Guelph ON Canada
Tel: 519.836.1291 **Fax:** 519.836.4878
Toll: 800.426.8979 (North America)
Email: sales@connecttech.com
www.connecttech.com