

FreeForm/104

FreeForm/104 is a PC/104 based card that features a reconfigurable FPGA for digital I/O and control applications.

Based on Xilinx's Spartan-3E, Connect Tech's FreeForm/104 offers off-the-shelf flexibility. The FPGA stored on-board in flash memory allows users to accommodate design changes at run-time, which is ideal for high speed and compute-intensive reconfigurable applications.

Customized FPGA configurations can be developed easily by the user with Xilinx's free ISE Webpack software at http://www.xilinx.com/ise/logic_design_prod/webpack.htm or through Connect Tech's engineering services.

The versatility and high speed processing core of FreeForm/104 makes it ideal for applications including DSP, software defined radio, aerospace, defense systems, computer hardware emulation, production or laboratory testing and industrial process monitoring and control.

Specifications

Programmable FPGA	Xilinx Spartan-3E, 500,000 gates, 360K RAM Standard FPGA Configurations: Digital I/O: 96 digital I/O (8255 compatible), 6 x 8254 counter/timers Digital I/O Opto-22: 48 Opto-22 (8255 compatible), 6 x 8254 counter/timers
Input Clock	66 MHz, internally scaleable
FPGA Code Storage	4 Mbit SPI Flash
Connectors	2 x 50 pin header: 48 regogammable 5V buffered I/O +/- 24mA drive current, each connector has 5V power and a ground pin 1 x 26 pin header: 6 bi-directional pins, 12 input pins, 6 ground pins, unbuffered 5V TTL PC/104 header: fully bi-directional, configurable as a master or a slave, 8 bit I/O, 12 address bits, all IRQ's are connected, DMA's 0-3
Programmable I/O	96 high current TTL/CMOS (48 per 50 pin connector), 6 TTL (26 pin connector)
Fixed I/O	12 TTL inputs (26 pin connector)
Interrupts	All PC/104 interrupts are connected to the FPGA
Temperature	Commercial Model: 0°C to 70°C (32°F to 158°F) Industrial Model: -40°C to 85°C (-40°F to 185°F) Humidity: 95% non-condensing Storage: -65°C to 150 °C
Power Requirements	+5VDC 0.75 W (0.150A@5V) average with standard design 2.75 W (0.550A@5V) maximum with I/O transfers at 10 Mbps Current requirements are design dependant
Dimensions	Length: 9.5885 cm/3.775" Width: 9.017 cm/3.55"
Weight	78 grams
Bus	PC/104 compatible or stand alone
System Requirements	Varies by configuration
Warranty and Support	Lifetime warranty and free technical support



Specifications subject to change without notice.
©2011, Connect Tech Inc. All trademarks are property of their respective holder.

Product Name: FreeForm/104
Part Number: FBG001/FBG006



FEATURES

- ✓ Customizable PC/104 board based on the Xilinx Spartan-3E
- ✓ FPGA configurable through JTAG or SPI flash (4Mb)
- ✓ External 5V power connection for stand alone usage
- ✓ Four user configurable LEDs and on-board reset switch
- ✓ Eight position rotary switch connected to FPGA

Connect Tech Inc.

42 Arrow Road, Guelph ON Canada
Tel: 519.836.1291 **Fax:** 519.836.4878
Toll: 800.426.8979 (North America)
Email: sales@connecttech.com
www.connecttech.com