

## Products in Family

DRSX1333RL/4GB (1 x 4GB 1Rx4 DIMM)  
 DRSX1333RL/8GB (1 x 8GB 2Rx4 DIMM)  
 DRSX1333RL/16GB (1 x 16GB 2Rx4 DIMM)



Features	Description
240-pin JEDEC-compliant DIMMs 133.35 mm wide by 30 mm high (1.181" x 5.25") Data Transfer Rate: 10.6 Gigabytes/sec Operating Voltage: 1.35 V $\pm$ 0.075 (1.5 V tolerant) Fully RoHS Compliant Thermal Sensor	Each DRSX1333RL upgrade consists of a single DDR3-1333 Registered DIMM that conforms to JEDEC's DDR3, PC3L-10600 standard. One 2K-bit EEPROM is used for Serial Presence Detect and a combination register/PLL with Address and Command Parity is also used. A thermal sensor accurately monitors the DIMM module and can prevent exceeding the maximum operating temperature of 95C.

Dataram Product	Oracle / Sun Product	Supported in these Oracle / Sun systems:
DRSX1333RL/4GB DRSX1333RL/8GB DRSX1333RL/16GB	X4910A X4911A Not Offered by Oracle	Sun Fire X4170 M2, X4270 M2, Sun Blade X6270 M2

### Notes

Tolerances on all dimensions except where otherwise indicated are  $\pm$ .13 (.005).

All dimensions are expressed in millimeters [inches]

