

## Products in Family


GRSX1066RQL/16GB (1 x 16GB 4Rx4 DIMM)  
 GRSX1066RQL/32GB (1 x 32GB 4Rx4 DIMM)



Features	Description
240-pin JEDEC-compliant DIMMs 133.35 mm wide by 30 mm high (1.181" x 5.25") Data Transfer Rate: 10.6 Gigabytes/sec Operating Voltage: 1.35 V ±0.075 (1.5 V tolerant) Fully RoHS Compliant Thermal Sensor	Each GRSX1066R upgrade consists of a single DDR3-1066 Registered ECC DIMM that conforms to JEDEC's DDR3, PC3L-8500 standard. One 2K-bit EEPROM is used for Serial Presence Detect and a combination register/PLL with Address and Command Parity is also used. A thermal sensor accurately monitors the DIMM module and can prevent exceeding the maximum operating temperature of 95C.

Dataram Product	Oracle / Sun Product	Supported in these Oracle / Sun systems:
GRSX1066RQL/16GB GRSX1066RQL/32GB	Not Offered by Oracle Not Offered by Oracle	Sun Blade X6270 M2

Front view




Notes

Tolerances on all dimensions except where otherwise indicated are ±.13 (.005).

All dimensions are expressed in millimeters [inches]

Back view



Side view

