


Clamp Spring - Spring type terminal blocks / WK series



WKA500



Pitch: 5.00mm

Approval	 	
Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	15A	24A
Conductor cross-section, solid (AWG/ mm ²)	28~12 / 0.5~2.5	
Conductor cross-section, flexible (AWG/ mm ²)	28~12 / 0.5~2.5	
Rated surge voltage (UL/IEC/Max.)	1.6 / 2.5 / 3 KV	
Wire strip length	5~6mm	
Single Pole	Cat. No.	
	WKA500-01X	
End Cover	WKA500C	



Optional color	Cat. No.
	WKA500-01X
	WKA500-01X-GN
	WKA500-01X-RD
	WKA500-01X-BL
	WKA500-01X-BK
	WKA500-01X-OR

Pole	Cat. No.
02	WKA500-02P
03	WKA500-03P
04	WKA500-04P
05	WKA500-05P
06	WKA500-06P
07	WKA500-07P
08	WKA500-08P
09	WKA500-09P
10	WKA500-10P
11	WKA500-11P
12	WKA500-12P
:	:
:	:

Optional color	Cat. No.
	WKA500-XXP
	WKA500-XXP-GN
	WKA500-XXP-RD
	WKA500-XXP-BL
	WKA500-XXP-BK
	WKA500-XXP-OR

TEL: +886-2-2908-0614**FAX:** +886-2-2908-8549**E-mail:** info@dinkle.com.tw