


Clamp Spring - Spring type terminal blocks / WK series



WKA508



Pitch: 5.08mm

Approval	 	
Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	15A	24A
Conductor cross-section, solid (AWG/ mm ²)	28~12 / 0.5~2.5	
Conductor cross-section, flexible (AWG/ mm ²)	28~12 / 0.5~2.5	
Rated surge voltage (UL/IEC/Max.)	1.6 / 2.5 / 3 KV	
Wire strip length	5~6mm	
Single Pole	Cat. No.	
	WKA508-01X	
End Cover	WKA500C	



Optional color	Cat. No.
●	WKA508-01X
●	WKA508-01X-GN
●	WKA508-01X-RD
●	WKA508-01X-BL
●	WKA508-01X-BK
●	WKA508-01X-OR

Pole	Cat. No.
02	WKA508-02P
03	WKA508-03P
04	WKA508-04P
05	WKA508-05P
06	WKA508-06P
07	WKA508-07P
08	WKA508-08P
09	WKA508-09P
10	WKA508-10P
11	WKA508-11P
12	WKA508-12P
:	:
:	:

Optional color	Cat. No.
●	WKA508-XXP
●	WKA508-XXP-GN
●	WKA508-XXP-RD
●	WKA508-XXP-BL
●	WKA508-XXP-BK
●	WKA508-XXP-OR

TEL: +886-2-2908-0614

FAX: +886-2-2908-8549

E-mail: info@dinkle.com.tw