



Clamp Spring - Spring type terminal blocks / WK series



WKV750A



Pitch: 7.50mm

Approval	 	
Technical Data	UL	IEC
Rated voltage	300V	450V
Rated current	15A	24A
Conductor cross-section, solid (AWG/ mm ²)	28~12 / 0.5~2.5	
Conductor cross-section, flexible (AWG/ mm ²)	28~12 / 0.5~2.5	
Rated surge voltage (UL/IEC/Max.)	1.6 / 2.5 / 4 KV	
Wire strip length	5~6mm	
Single Pole	Cat. No.	
	WKV750A-01X	
End Cover	WKV500AC	



Optional color	Cat. No.
●	WKV750A-01X
●	WKV750A-01X-GN
●	WKV750A-01X-RD
●	WKV750A-01X-BL
●	WKV750A-01X-BK
●	WKV750A-01X-OR

Pole	Cat. No.
02	WKV750A-02P
03	WKV750A-03P
04	WKV750A-04P
05	WKV750A-05P
06	WKV750A-06P
07	WKV750A-07P
08	WKV750A-08P
09	WKV750A-09P
10	WKV750A-10P
11	WKV750A-11P
12	WKV750A-12P
:	:
:	:

Optional color	Cat. No.
●	WKV750A-XXP
●	WKV750A-XXP-GN
●	WKV750A-XXP-RD
●	WKV750A-XXP-BL
●	WKV750A-XXP-BK
●	WKV750A-XXP-OR

TEL: +886-2-2908-0614**FAX:** +886-2-2908-8549**E-mail:** info@dinkle.com.tw