


Clamp Spring - Spring type terminal blocks / WK series



WKA116



Pitch: 10.16mm

Approval	 	
Technical Data	UL	IEC
Rated voltage	300V / 600V	750V
Rated current	15A / 5A	24A
Conductor cross-section, solid (AWG/ mm ²)	28~12 / 0.5~2.5	
Conductor cross-section, flexible (AWG/ mm ²)	28~12 / 0.5~2.5	
Rated surge voltage (UL/IEC/Max.)	2.2 / 3 / 4 KV	
Wire strip length	6~7mm	
Single Pole	Cat. No.	
	WKA116-01X	
End Cover	WKA500C	



Optional color	Cat. No.
●	WKA116-01X
●	WKA116-01X-GN
●	WKA116-01X-RD
●	WKA116-01X-BL
●	WKA116-01X-BK
●	WKA116-01X-OR

Pole	Cat. No.
02	WKA116-02P
03	WKA116-03P
04	WKA116-04P
05	WKA116-05P
06	WKA116-06P
07	WKA116-07P
08	WKA116-08P
09	WKA116-09P
10	WKA116-10P
11	WKA116-11P
12	WKA116-12P
:	:
:	:

Optional color	Cat. No.
●	WKA116-XXP
●	WKA116-XXP-GN
●	WKA116-XXP-RD
●	WKA116-XXP-BL
●	WKA116-XXP-BK
●	WKA116-XXP-OR

TEL: +886-2-2908-0614

FAX: +886-2-2908-8549

E-mail: info@dinkle.com.tw