



DIN Rail terminal blocks / DK..D series



DK4D



Approval		
Technical Data	UL	IEC
Rated voltage	600V	1000V
Rated current	30A	32A
Conductor cross-section, solid (AWG / mm ²)	22~10 / 0.5~4	
Conductor cross-section, flexible (AWG / mm ²)	22~10 / 0.5~4	
Rated impulse withstand voltage	6KV	
Torque (N-m)	0.6	
Screw	M3	
Wire strip length	9~11mm	
Insulating material	PA	
TxHxW (mm)	6.1x39.6x40.3	
Optional color	Cat. No.	
●	DK4D-RD	
●	DK4D-BL	
●	DK4D-BK	
●	DK4D-OR	



	Accessories	Cat. No.
End cover		DK4NC
Partition		
Small partition		DKNSPS-001
Insertion bridge	2 way	DSS4N-02P
	3 way	DSS4N-03P
	4 way	DSS4N-04P
	10 way	DSS4N-10P
Insertion bridge	2 way	CSC-402N
	3 way	CSC-403N
	4 way	CSC-404N
	10 way	CSC-410N
Screw-on bridge	2 way	
	3 way	
	4 way	
	10 way	
Marking label		TM27
Mounting Rail		TS-35 / TS-32
Tool		0.5x3mm