



- A. 10mm (.395") snap stud to ground work surface.
- B. Molded in black thermoplastic elastomer.
- C. Ring terminal, .200" ID, (#10).
- D. Extra ring terminal included for customizing length.
- E. The <u>09826</u> has a 1 megohm resistor between the snap and ground, with banana jacks at ground potential. The <u>09825</u> has no resistor between snap and ground, with banana jacks also at ground potential.
- F. Wire is autosplice crimped to secure it inside of the mold.

- G. High flex strand copper, 20 gauge, with PVC insulated jacket
 - 09825 green insulation with yellow stripe 09826 black insulation
 - OD = .100"
- H. Dual banana jacks at ground potential (.162" .164" ± .002" ID).
- Desco and ground symbol molded into the plastic.
- J. Date coded to show month and year of manufacture.

Surface and Writ Strap to Common Point

COMMON POINT GROUND

BENCH MAT

Grounds ESD Work



ITEM	DESCRIPTION
<u>09825</u>	No Resistor - Green Wire with Yellow Stripe
09826	One Megohm Resistor to Mat - Black Wire

Specifications and procedures subject to change without notice.



GROUND CORD, COMMON POINT, WORKMAT

DESCO WEST:3651 WALNUT AVE., CHINO, CA 91710 WEB SITE: Desco.com PHONE (909) 627-8178 FAX (909) 627-7449 FAX REQUEST (909) 627-7126

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407 PHONE (781) 821-8370 FAX (781) 575-0172

DRAWING NUMBER 09825

DATE: February 2010